HGA36025

Circuit breaker, PowerPacT H, thermal magnetic, I-Line, 25A, 3 pole, 18 kA, 600 VAC, phase ABC, 80% rated





Main	
Product or component type	Circuit breaker
Range of product	PowerPact H
Trip Unit Type	Thermal-magnetic
Breaking capacity code	G

Complementary

Line Rated Current	25 A	
Number of Poles	3P	
Interrupt Rating	20 KA at 500 V DC	
	65 KA 240 V AC	
	35 KA 480 V AC	
	18 KA 600 V AC	
	20 kA 250 V DC	
[Ue] rated operational voltage	250 V DC	
	600 V AC	
	500 V DC	
Continuous current rating	80 %	
Mounting mode	I-Line	
Electrical connection	I-Line connection line	
	Lugs load	
Magnetic hold current	350 A	
Magnetic tripping current	750 A	
Wire Gauge	AWG 14AWG 3/0 aluminium/copper	
Tightening torque	44.25 lbf.in (5 N.m) 0.000.15 in² (2.595 mm²) AWG 14AWG 3/0)	
Phase	ABC	
Height	9.73 in (247.14 mm)	
Width	4.48 in (113.79 mm)	
Maximum Depth	4.8 in (121.92 mm)	

Environment

Product certifications	IEC UL Listed CSA CE
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	01117 - HG, HJ, JG, JJ I-LINE BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901700562
Nbr. of units in pkg.	1
Package weight(Lbs)	5.41 lb(US) (2.45 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Package 1 Height	6.30 in (16.002 cm)
Package 1 width	8.30 in (21.082 cm)
Package 1 Length	15.10 in (38.354 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	[™] REACh Declaration
EU RoHS Directive	Compliant EPEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

	· ·
Warranty	18 months