

# WBR20-R

## Item Description

Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Weather-Resistant, Indented Face, 20 Amp, 125 Volt, Back or Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - Red



UPC Code: 07847790771

Country Of Origin: Mexico

NEMA:  
5-20R



## Technical Information

### AC Horsepower Rating

**Horsepower Rating:** 1 HP

### Electrical Specifications

**Amperage:** 20 A

**Dielectric Voltage:** Withstands 3000 V minimum

**Grounding:** Self-Grounding

**Pole:** 2

**Temperature Rise:** Max 30 °C after 250 cycles OL at 200 percent rated current

**Voltage:** 125 VAC

**Wire:** 3

### Environmental Specifications

**Flammability:** Rated V-0 per UL 94

**Operating Temperature:** -40°C to 75°C

### Material Specifications

**Body Material:** PBT Polyester Blend

**Face Material:** PBT Polyester Blend

**Ground Clips:** Brass

**Ground Contacts:** 0.030" Brass

**Grounding Screw:** #8 hex head, triple drive Brass

**Line Contacts:** 0.030" Phosphor Bronze

**Mounting Screws:** Triple-Drive Plated Steel

**Strap Material:** Steel

**Terminal Clamps:** Brass

**Terminal Screws:** #8 Triple-Drive Brass

### Mechanical Specifications

**Product ID:** Ratings are permanently marked on device

**Terminal Accom.:** #14 AWG - #10 AWG

**Terminal ID:** Brass - Hot, Green - Ground, Silver - Neutral

**Termination:** Back or Side Wire

**Wire Type:** Stranded or Solid

### Product Features

**Color:** Red

**Color / Feature:** Black

**Device Type:** Duplex Receptacle Outlet

**Feature:** Weather-Resistant

**Feature 2:** Weather-Resistant

**Feature 4:** Indented Face

**Grade:** Heavy-Duty Industrial Specification Grade

**NEMA:** 5-20R

### Standards & Certifications

**ANSI:** C-73

**Applicable Standards:** UL 498, Fed Spec W-C-596, CSA C22.2. No. 42

**Certification/Listing:** cULus, NOM-ANCE

**NEMA:** WD 1 & WD 6

**RoHS:** RoHS Compliant

## Patents\*

CA2483480


US6743029

MX257790

US8684771

MX321216

\*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.



Drawing Applies to 15 & 20A Devices

**SPECIFICATION SUBMITTAL**

JOB NAME:		CATALOG NUMBERS:	
<input type="text"/>		<input type="text"/>	<input type="text"/>
JOB NUMBER:		<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

Visit our Website at: [www.leviton.com](http://www.leviton.com)

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

