# QDA32200

Circuit breaker, PowerPact Q, I-Line, thermal magnetic, 200A, 3 pole, 25 kA@240 VAC, phase ABC





Main	
Product or component type	Circuit breaker
Range of product	PowerPact Q
Trip unit technology	Thermal-magnetic

Complementary

200 A
240 V AC
3
25 kA 240 V AC
80 %
D
I-Line
Lugs load AWG 4300 kcmil aluminium/copper I-Line connection line ABC
ABC
1200 A
2400 A
6.47 in (164.34 mm)
4.5 in (114.30 mm)
3.93 in (99.82 mm)
247.82 lbf.in (28 N.m) 0.040.16 in² (25100 mm²) AWG 4300 kcmil)

#### **Environment**

Product certifications	IEC CSA UL Listed

#### Ordering and shipping details

01023 - Q2 BREAKER & SWITCH	
DE2	
00785901417842	
1	
6.75 lb(US) (3.06 kg)	
Yes	
MX	
	DE2 00785901417842 1 6.75 lb(US) (3.06 kg) Yes

# Packing Units

•	
Unit Type of Package 1	PCE
Package 1 Height	6.00 in (15.24 cm)
Package 1 width	7.70 in (19.558 cm)
Package 1 Length	12.50 in (31.75 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	256
Package 2 Weight	1752.00 lb(US) (794.693 kg)
Package 2 Height	40.00 in (101.6 cm)
Package 2 width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☐ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	
Halogen content performance	Halogen free product	

### Contractual warranty

14/	40
Warranty	18 months
•	