

The Smart Choice in Tamper-Resistant Receptacles

Our Expanded Line Has Your Code Needs Covered



Plug Into Safety[®] with Leviton's Line of Tamper-Resistant (TR) Receptacles

Child safety is a priority at Leviton, where we've increased our Tamper-Resistant (TR) Receptacle selection. Since 2008, the National Electrical Code[®] has required tamper-resistant receptacles in new or renovated housing. The 2011 NEC also mandates TR Receptacles in childcare facilities, guest rooms and guest suites as well as when replacing existing receptacles in required locations. TR devices have a shutter mechanism inside the receptacle that blocks access to the contacts from most foreign objects. Leviton leads the way in safety advances with a wide range of tamper-resistant devices in Residential and Commercial Grades. To help you meet the demand for upgrades, we provide a handy cross-reference of standard and TR catalog numbers on the following page.



Features and Benefits:

- Shutter mechanism inside the receptacle blocks access to the contacts unless a two-prong plug is inserted, helping ensure hairpins, keys, etc., will be locked out
- TR symbol on residential receptacles assures they meet the NEC requirement
- TR Selection includes Residential and Commercial Grade receptacles
- Heavy-duty construction offers long, trouble-free service life
- Limited Two-Year Warranty

Applications:

- New or renovated single- and multi-family housing
- Schools, libraries, childcare facilities
- Guest rooms and guest suites

Agency Standards:

UL Listed: TR and Weather Resistant Receptacles
TWR15 and TWR20 (File #E-13399)
TR Combination Devices (File #E-7458)
SmartlockPro® TR GFCI (File #E-48380)

CSA Certified: All TR Devices (File #152105)

STANDARD AND TR RECEPTACLE CROSS-REFERENCE

RESIDENTIAL RECEPTACLES
Duplex Receptacles
NEMA 5-15R and 5-20R

Description	Standard Receptacle Catalog Number	TR Receptacle Catalog Number	Rating	TR Color* (Basic Cat. No. denotes Brown)
Duplex Receptacle, Quickwire Push-in and Side Wired	5320	T5320	15A-125V	W, I, A, T, E
Duplex Receptacle, Side Wired	N/A	T5820	20A-125V	W, I, E, GY, T
Decora® Duplex, Quickwire Push-in and Side Wired	5325	T5325	15A-125V	W, I, A, T, E
Decora Duplex Receptacle, Side Wired	N/A	T5825	20A-125V	W, I, E, GY, T

Combination Devices

Decora LED Guide Light/Receptacle	N/A	T6525	15A-125V	W, I, A, T
Single Pole Switch/Receptacle with Ground Screw	5225	T5225	Switch: 15A-120V Receptacle: 15A-125V	W, I, A, T
Decora Single Pole Switch/Receptacle with Ground Screw	5625	T5625	Switch: 15A-120V Receptacle: 15A-125V	W, I, A, T, E
Combination GFCI Single Outlet w/Sensor Controlled Guide Light	7591	T7591	15A-125V @ Receptacle, 20A-125V @ Feed-Through	W, I, A, T (n/a in Brown)
Combination GFCI Single Outlet w/Switch	7229	T7299	15A-125V @ Receptacle, 20A-125V @ Feed-Through	W, I, A, T (n/a in Brown)

SmartlockPro® Slim GFCI – Back and Side Wired

GFCI with LED Indicator Light	7599	X7599	15A-125V @ Receptacle, 20A-125V @ Feed-Through	W, I, GY, E, T
GFCI with LED Indicator Light	7899	X7899	20A-125V @ Receptacle, 20A-125V @ Feed-Through	W, I, GY, E, T

COMMERCIAL GRADE RECEPTACLES
Straight Blade Receptacles

Description	Standard Receptacle Catalog Number	TR Receptacle Catalog Number	Rating	TR Color* (Basic Cat. No. denotes Brown)
Duplex Receptacle, Back and Side Wired	BR15	TBR15	15A-125V	W, I, T, GY, E
Duplex Receptacle, Back and Side Wired	BR20	TBR20	20A-125V	W, I, T, GY, E
Duplex Receptacle, Side Wired	CR15	CR15S	15A-125V	W, I, T, GY
Decora Plus Duplex Receptacle, Side Wired	16242	DR15S	15A-125V	W, I, T, GY, E
Decora Plus Duplex Receptacle, Back and Side Wired	16252	TDR15	15A-125V	W, I, GY, E
Decora Plus Duplex Receptacle, Back and Side Wired	16352	TDR20	20A-125V	W, I, T, GY, E
Single Receptacle, Side Wired	5015	T5015	15A-125V	W, I, T, GY, E
Single Receptacle, Side Wired	5801	T5020	20A-125V	W, I, T
Duplex Floor Box Receptacle, 2-Pole, 3-Wire, Self-Grounding with Brass Plate	N/A	25249-TFB	15A-125V	I
Duplex Floor Box Receptacle, 2-Pole, 3-Wire, Self-Grounding with Nickel Plate	N/A	25249-TFN	15A-125V	I

Weather Resistant Receptacles

Residential Grade: Duplex Receptacle, 2-Pole, 3-Wire, Self-Grounding	N/A	W5320-T	15A-125V	W, GY
Residential Grade: Duplex Receptacle, 2-Pole, 3-Wire, Self-Grounding	N/A	W5820-T	20A-125V	W
Duplex Receptacle, 2-Pole, 3-Wire, Self-Grounding	WBR15 (Yellow only)	TWR15	15A-125V	W, GY (n/a in Brown)
Duplex Receptacle, 2-Pole, 3-Wire, Self-Grounding	WBR20 (Yellow only)	TWR20	20A-125V	W, GY (n/a in Brown)
Outdoor Grade SmartlockPro GFCI Receptacle, Back and Side Wired, with LED Indicator Light	W7599	W7599-TR	15A-125V @ Receptacle, 20A-125V Feed-Through	W, I, E (n/a in Brown)
Outdoor Grade SmartlockPro GFCI Receptacle, Back and Side Wired, with LED Indicator Light	W7899	W7899-TR	20A-125V @ Receptacle, 20A-125V Feed-Through	W, I, E (n/a in Brown)

* TR Color: Basic Cat. Nos. denote Brown, unless otherwise noted. For color selection, add suffix to catalog number as follows:
White (-W), Ivory (-I), Almond (-A), Light Almond (-T), Gray (-GY) and Black (-E).

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747-3138
Telephone: 1-800-323-8920 • FAX: 1-800-832-9538 • Tech Line (8:30AM-7:00PM E.T. Monday-Friday): 1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9
Telephone: 1-800-469-7890 • FAX: 1-800-563-1853

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290
Tel. (+52) 55-5082-1040 • Fax: (+52) 55-5386-1797
www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2011 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.



B-1300E/B11-dp