


EVT002

ADOGH040VAS0010E04

Connection technology

Product characteristics

Socket

For sensors with

M12 connector

Free from silicone

gold-plated contacts

For hygienic and wet areas in the food industry

Electrical data

Electrical design		AC/DC
Operating voltage	[V]	250 AC / 300 DC
Current rating	[A]	4
Protection class		II

Environment

Ambient temperature	[°C]	-25...100, cULus: max. 50 °C
Ambient temperature (moving)	[°C]	5...100, cULus: max. 50 °C
Protection		IP 65 / IP 67 / IP 68 / IP 69K

Mechanical data

Design		straight
Material body		housing: PVC orange; sealing: EPDM
Material nut		stainless steel 316L / 1.4404
Tightening torque for knurled nut [Nm]		0.6...1.5
Drag chain suitability		Bending radius for flexible applications: min. 10 x cable diameter max. 3.3 m/s for a horizontal travel length of 5 m and max. acceleration of 5 m/s² Travel speed: Bending cycles: Torsional strain: > 1 million ± 180 °/m
Weight	[kg]	0.376

Electrical connection

Connection		PVC cable / 10 m; 4 x 0.34 mm ² (42 x Ø 0.1 mm); Ø 4.9 mm
Sheath color		orange

Wiring





EVT002

ADOGH040VAS0010E04

Connection technology

Core colors

- BK black
- BN brown
- BU blue
- WH white



Remarks

Pack quantity	[piece]	1
---------------	---------	---