



SKU: AU-2/0

UPC: 0783669000740

Features & Benefits:

Description: Aluminum Mechanical Lug, Conductor Range 2/0-14, 2 Ports, 1 Hole, 1/4in Bolt Size, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	2
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	2

Dimensions

Dimension G (IN)	0.422
Drive Size Main	3/16
Drive Type Main	Internal Hex
Height (IN)	0.794
Height BX (IN)	2.25
Height (mm)	20.1676
Length (IN)	1.469
Length (mm)	37.3126
Mounting Hole Diameter (IN)	0.272
Mounting Hole Diameter (mm)	6.9088
Mounting Hole Spacing (mm)	0
Tang Length (IN)	0.844
Tang Length (mm)	21.4376
Tang Thickness (IN)	0.187
Tang Thickness (mm)	4.7498
Tang Width (IN)	1.25
Tang Width (mm)	31.75
Weight (LB)	0.155
Weight BX (LB)	1.992
Width (IN)	1.25
Width BX (IN)	5
Width (mm)	31.75

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum

Wire Binding Hardware Finish
Wire Binding Hardware Material

Tin
Aluminum

Additional Technical Specifications

Conductor Type Stranded

Bolt and Screw Sizes

Mounting Bolt/Stud Size 1/4
Number of Wire Binding Screws per Port 1
Wire Binding Screw Size 7/16
Wire Binding Torque 120

General

Bag Quantity 1
Carton Quantity Description STD PACK QTY 12
Direct Burial No
Dual Rated Yes
NEMA Code S-588-3
UPC Code 78366900074

Testing Standards

CSA File Number LR-29601
CSA Standard C22.2 No. 65-03
Prop65 Compliance This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator IND
UL Control Number 453G
UL / CULUS Specification UL 486A/B Listed
UL File Number E6207

Environment and Temperature

Temperature Rating 90°C

Color

Color Silver

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load) NA
Conductor Range AL Stranded (Primary, run, main, line) 2/0 Str - 14 Str
Conductor Range AL Stranded (Secondary, tap, load) NA
Conductor Range CU Solid (Primary, run, main, line) 10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load) NA
Conductor Range CU Stranded (Primary, run, main, line) 2/0 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load) NA
Conductor Range AL Solid (Primary, run, main, line) 10 Sol - 14 Sol
Wire Combinations NA

Voltage

Voltage Rating

35 kV