



SKU: BGC-2PS-DB

UPC: 0783669001235

Features & Benefits:

Description:Permaground Bronze Ground Clamp, Conductor Range 2-10, Pipe Sizes 1/2 to 1in, Ground Rod Sizes 1/4 to 1in, Rebar Sizes #3-#8, Parallel Lay-in, Direct Bury

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Parallel

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	2 Sol - 10 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2 Str - 10 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Ground Rod Size	1/4
NPS/IPS Pipe Size	1/2
Rebar Size(s) Main	#4 (1/2)
Wire Combinations	(2) 8 Sol

Dimensions

Drive Size Main	NA
Drive Type Main	Internal Hex
Height (IN)	2.338
Height BX (IN)	2
Height (mm)	59.3852
Length (IN)	2.246
Length (mm)	57.0484
Weight (LB)	0.25
Weight BX (LB)	6.25
Width (IN)	0.668
Width BX (IN)	6.188
Width (mm)	16.9672

Material and Finish

Clamping Hardware Material	Stainless steel
----------------------------	-----------------

Conductor Material	Copper
Connector Finish	Bright Dip
Insulation	NA
Material	Bronze
Wire Binding Hardware Material	Stainless steel

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Clamping Bolt Size	1/4-20
Clamping Bolt Size (mm)	36068
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	NA

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-2
UPC Code	78366900123

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	8M24
UL / CULUS Specification	UL 467 Listed
UL File Number	E198108