



**SKU:** CA4RP

**UPC:** 0783669021059

**Features & Benefits:**

**Description:** Aluminum Box-Type Mechanical Lug, Conductor Range 2-14 CU, 2-12 AL, 1 Hole, Round Boss, Tin Plated

## Specs

### Dimensions

Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.685
Height BX (IN)	2.25
Height (mm)	17.399
Length (IN)	0.469
Length (mm)	11.9126
Mounting Bolt/Stud Size (mm)	26212.8
Mounting Hole Diameter (IN)	0.164
Mounting Hole Diameter (mm)	4.1656
Mounting Hole Spacing (mm)	0
Size of Boss (IN)	0.229
Size of Boss (mm)	5.8166
Weight (LB)	0.01
Weight BX (LB)	1.98
Width (IN)	0.487
Width BX (IN)	5
Width (mm)	12.3698

### Additional Class Attributes

Anti-Turn Key	No
Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Tap
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	1
Style of Boss	Round

### Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

## Additional Technical Specifications

Conductor Type	Solid
----------------	-------

## Bolt and Screw Sizes

Mounting Bolt/Stud Size	#10-32
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	3/8
Wire Binding Torque	4 - 6 AWG = 45

## General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 100
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-3
UPC Code	78366902105

## Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL / CULUS Specification	UL 486A/B Recognized
UL File Number	E6207

## Environment and Temperature

Temperature Rating	75°C
--------------------	------

## Color

Color	Silver
-------	--------

## Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	2 Str - 12 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 12 Sol
Wire Combinations	NA

## Voltage



**Voltage Rating**

35 kV