



SKU: CDT-307-8

UPC: 0783669946772

Features & Benefits:

Description:Permaground Copper Grounding H-Tap, Double Tab, Main Conductor Range 4/0-2/0, Tap Range 4/0-2/0

Specs

Additional Class Attributes

Barrel Marking	Hard
Fixing Type	NA
ILSCOs Die Index Number	NA
Installing Dies	D3

Dimensions

Height (IN)	0.906
Height BX (IN)	3.625
Length (IN)	1.375
Weight (LB)	0.178
Weight BX (LB)	4.704
Width (IN)	1.062
Width BX (IN)	6.375

Material and Finish

Conductor Material	Copper
Connector Finish	Bare
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	Yes
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366994677

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

Testing Standards

CSA File Number	NA
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	8M24
UL / CULUS Specification	UL 467 Listed
UL File Number	E158587

Environment and Temperature

Temperature Rating	NA
--------------------	----

Color

Color	Copper
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4/0 Str - 2/0 Str
Conductor Range CU Stranded (Secondary, tap, load)	4/0 Str - 2/0 Str
Conductor Range AL Solid (Primary, run, main, line)	NA