



SKU: CP-0

UPC: 0783669030105

Features & Benefits:

Description: Copper Post Connector, Conductor Range 1/0-8, 5/16in Bolt Size, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	No
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Number of Poles	1
Number of Ports / Wireways	1

Dimensions

Drive Size Main	1/4
Drive Type Main	Internal Hex
Height (IN)	0.763
Height BX (IN)	2.25
Height (mm)	19.3802
Length (IN)	1.609
Length (mm)	40.8686
Weight (LB)	0.08
Weight BX (LB)	5.475
Width (IN)	0.73
Width BX (IN)	5
Width (mm)	18.542

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	5/16
-------------------------	------

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	NA
Wire Binding Torque	8 - 14 AWG = 50

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366903010

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	2 Sol - 10 Sol
Conductor Range CU Stranded (Primary, run, main, line)	1/0 Str - 10 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Wire Combinations	NA

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Copper
-------	--------

Voltage

Voltage Rating	35 kV
----------------	-------