



SKU: CSWS-250-58

UPC: 0783669640816

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 250, 1 Hole, 5/8in Bolt Size, Standard Barrel, Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-62
ILSCOs Die Index Number	I-62
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	1
Sight Window	Yes
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	1.063
Barrel Length (mm)	27.0002
Dimension G (IN)	0.671
Dimension G (mm)	17.0434
Height (IN)	0.791
Height BX (IN)	2.25
Height (mm)	20.0914
Inside Diameter (IN)	0.593
Inside Diameter (mm)	15.0622
Length (IN)	3.031
Length (mm)	76.9874
Mounting Hole Diameter (IN)	0.656
Mounting Hole Diameter (mm)	16.6624
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	0.751
Outside Diameter (mm)	19.0754
Strip Length (mm)	28.575
Tang Length (IN)	1.437
Tang Length (mm)	36.4998
Tang Thickness (IN)	0.157
Tang Thickness (mm)	3.9878
Tang Width (IN)	1.088

Tang Width (mm)	27.6352
Weight (LB)	0.142311446170124
Weight BX (LB)	1.445
Width (IN)	1.088
Width BX (IN)	5
Width (mm)	27.6352

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	250 kcmil - 1/0 Str
Flex Conductor Range	4/0 G,H,I,K,M,DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Flex
----------------	------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366964081

Bolt and Screw Sizes

Mounting Bolt/Stud Size	5/8
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	453G
UL / CULUS Specification	UL 467 Listed
UL File Number	E6207

Environment and Temperature



Temperature Rating

90°C

Color

Color

Silver

Color Code

Yellow

Voltage

Voltage Rating

35 kV