

IMAGE  
COMING  
SOON

**SKU:** SLSS12-1/0SSP-Z

**UPC:** 0783669820713

**Features & Benefits:**

**Description:** Streetwise Street Light Connector, Dual Rated, Conductor Range 1/0-14, 1 Port Line Side, 2 Ports Load Side, ANSI, With De-Ox

## Specs

### Additional Class Attributes

Connection	Mechanical
Contains DE-OX®	Yes
Number of Conductors	3
Number of Poles	1
Number of Ports Tap	2
Number of Ports / Wireways	3
Replacement Part(s)	R7188C00A - PLUG, WIRE SEAL, R7189C00A - ROCKET SEAL
Type of Accessory	NFL3

### Dimensions

Drive Size Main	3/16
Drive Size Tap	3/16
Drive Type Main	Internal Hex
Drive Type Tap	Internal Hex
Height (IN)	7.51
Height BX (IN)	2.75
Length (IN)	1.995
Weight (LB)	0.6056
Weight BX (LB)	0.7706
Width (IN)	2.395
Width BX (IN)	5

### Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	TPE (thermoplastic elastomer)
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	3/8

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Direct Burial	Yes
Dual Rated	Yes
NEMA Code	S-569-2
UPC Code	78366982071

### Testing Standards

ANSI Specification	ANSI C119.1
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
UL Control Number	NA
UL File Number	NA

### Environment and Temperature

Temperature Rating	90°C
Water tight	Yes

### Color

Color	Black
-------	-------

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range AL Stranded (Primary, run, main, line)	1/0 Str - 14 Str
Conductor Range AL Stranded (Secondary, tap, load)	1/0 Str - 14 Str
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	1/0 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	1/0 Str - 14 Str
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol

### Voltage

Voltage Rating	600 V
----------------	-------