



Fig. 1



Fig. 2

SKU: SSKC-6-Z

UPC: 0783669857603

Features & Benefits:

Description: Watertight Underground Splice Kit, Dual Rated, Conductor Size 6, Includes (1) SS-350-Z Cover and (1) ASN-6 Sleeve

Specs

Additional Class Attributes

Includes	(1) SS-350-Z, (1) ASN-6
Number of Conductors	2

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	6 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	6 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	NA

Dimensions

Height (IN)	2.2
Height BX (IN)	3.75
Height (mm)	55.88
Length (IN)	14
Length (mm)	355.6
Weight (LB)	0.23798312612136
Weight BX (LB)	1.7092
Width (IN)	4
Width BX (IN)	6.375
Width (mm)	101.6

Material and Finish

Conductor Material	Copper
Insulation	EPDM
Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Direct Burial	Yes
Dual Rated	Yes
NEMA Code	S-569-1
UPC Code	78366985760

Testing Standards

Prop65 Compliance

WARNING: Cancer and Reproductive Harm -
www.P65warnings.ca.gov

Environment and Temperature

Temperature Rating	90°C
Water tight	Yes

Color

Color	Silver
-------	--------

Voltage

Voltage Rating	600 V
----------------	-------