

UWZ48E Series Flush Mount with Bracket



- Fits into 1.79" x 1.79" (45.5 mm x 45.5 mm) cut-out
- Flush mount panel thickness up to 0.35" (9 mm)
- Fits square or round 72 mm opening with optional bezel
- Unit is secured by a plastic slip-on retaining bracket

Model #	Input Voltage
UWZ48E-120U	120 VAC, 60 Hz
UWZ48E-120/50U	120 VAC, 50 Hz
UWZ48E-220/50U	220 VAC, 50 Hz
UWZ48E-24U	24 VAC, 60 Hz
UWZ48E-24/50U	24 VAC, 50 Hz
UWZ48E-240U	240 VAC, 60 Hz

Rating:
Bezel: 1.89" x 1.89" (48 mm x 48 mm)

Capacity: 99,999.99 hours

Digits: 0.16" high numerals

Termination:

Combination ¼" spade and screw clamp

Operating Temperature: -40°F to 160°F
(-40°C to 72°C)

Accuracy synchronous to network


UWZ48V Series DIN Rail Mount



- Snap-on socket base
- Unit can be fitted to DIN Rail quickly and easily

Model #	Input Voltage
UWZ48V-24U	24 VAC, 60 Hz
UWZ48V-120U	120 VAC, 60 Hz

Rating:
Bezel: 1.89" x 1.89" (48 mm x 48 mm)

Capacity: 99,999.99 hours

Digits: 0.16" high numerals

Termination: Screw lugs

Operating Temperature:

-40°F to 160°F (-40°C to 72°C)

Accuracy synchronous to network


UWZ52E Series Flush Mount with Bracket



- Fits into 1.79" x 1.79" (45 mm x 45 mm) cut-out
- Round face fastened with a plastic slip-on retaining bracket
- Flush mount panel thickness up to 0.35" (9 mm)

Model #	Input Voltage
UWZ52E-120U	120 VAC, 60 Hz

Rating:
Bezel: 2.28" (58 mm) diameter

Capacity: 99,999.99 hours

Digits: 0.16" high numerals

Termination: Combination ¼"

spade and screw clamp

Operating Temperature: -40°F to 160°F (-40°C to 72°C)

Accuracy synchronous to network


UWZ48E Series Accessories Bezels

Model #	Description	Color
BEZ-55BLACKU	55 mm Bezel	Black
BEZ-55GRAYU	55 mm Bezel	Gray
BEZ-72U	72 mm Bezel	Gray
BEZ-72PU	72 mm Bezel with 3 pins for round 3-bolt hole openings	Gray