



E.



F.



G.

P1100 Series Portable Outdoor Timers

- Control filter pumps
- Turn outdoor decorations, engine block heaters, and other appliances ON/OFF

	Model #	Description	Plug & Receptacle	Cord Length
E.	P1101	24-Hour timer	5-15	22"
F.	P1121	24-Hour timer	5-15	13"
G.	P1131	Heavy-duty 24-Hour timer with twist-lock plug and receptacle	5L-20	22"

Ratings:
Enclosure: Outdoor grade plastic Dimensions: 5" (12.7 cm) H x 5 1/2" (13.97 cm) W x 3 3/4" (9.52 cm) D
Cord: 3 wire, outdoor grade with grounded plug
Timer: 24-Hour with 23 1/2 hour maximum ON time. Two ON, two OFF trippers standard. Accepts up to 12 sets of trippers.
Switch Rating:
 P1101 and P1121: 15 A (1800 W), Resistive or Tungsten, 1 HP Air Conditioner, (15 FLA, 90 LRA), Motor Load
 P1131: 20 A Resistive, 1 HP, (15 FLA, 90 LRA) Motor Load
Warranty: 1 year

For replacement parts, trippers and accessories, see page 153.

P1200 Series Two-Circuit Portable Outdoor Timers

- Incorporate a plug-in for a timed circuit and a plug-in for a live circuit
- Built-in GFCI protected circuits and three-prong grounded plug for time switch supply
- Great for above ground pool pumps, lights, or fountains
- Type 3R plastic Indoor/Outdoor enclosure



H.



J.

	Model #	Photo Control	Plug & Receptacle
H.	P1251P	Yes	5-15
J.	P1261P	No	5-15

Ratings:
Timer: 24-Hour with 23 1/2 hour maximum ON time. Two ON, two OFF trippers standard. Accepts up to 12 sets of trippers.
Switch Rating:
 15 A (1800 W), Resistive or Tungsten, 1 HP (15 FLA, 90 LRA) 120 VAC Motor Load
Enclosure Dimensions: 9 3/8" H x 5 1/2" W x 3 3/4" D
Cord: 3 wire, outdoor grade, 24" with grounded plug
Warranty: 1 year

For replacement parts, trippers and accessories, see page 153.