




MOTOR FINISH

 Distressed Black

BLADE FINISHES

Walnut, Satin Black

 Damp Rated

 Dimmable

 LED Light Kit

AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	RPM Revolutions Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
4678	154	62	75

CFM (Low)	1526
RPM (Low)	52
Watts (Low)	11

SPECIFICATIONS

Light Source			
Downlight Included	Yes	Downlight Option	Integrated
Watts (High)	62	Watts (Low)	11
Dimmable	Yes	Lamp Included	Integrated
Light Source	LED	# of Bulbs/LED Modules	1
Optional Light Kit Available	Integrated		
Photometrics			
Color Rendering Index	90	Delivered Efficacy (Lumens/Watt)	80
Kelvin Temperature	3000K		
Electrical			
Amps (High)	0.52	Amps (Low)	0.23
Motor Size	172MM X 12MM	Motor Type	AC Induction
Supply Wire (Degrees)	90		
Dimensions			
Downrod 1	1.00" OD X 4.50"	Downrod 1 - Measurement A	14.25"
Downrod 1 - Measurement B	10.00"	Downrod 1 - Measurement C	8.00"
Base Backplate	6.00 DIA	Weight	20.90 LBS
Mounting/Installation			
Minimum Distance from Fan to Floor	7.0 feet	Interior/Exterior	Exterior
Lead Wire Length	78"	Location Rating	Damp
Mounting Style	Downrod	Mounting Weight	16.55 LBS

FIXTURE ATTRIBUTES

Product/Ordering Information			
SKU	300241DBK	Finish	Distressed Black
Style	Lodge / Country	UPC	783927000963

Housing			
Fan Primary Control System	65K Cooltouch - Full Function	Remote Included	Yes
Diffuser Description	Etched Cased Opal	Primary Material	STEEL
Max Stem Tilt	22.00		
Blade Finish & Specs			
Blade Finish 1	Walnut	Blade Finish 2	Satin Black
Blade Material	ABS	Blade Pitch	12
Blade Sweep	52	Blades Included	Yes
Blades Reversible	Yes	Number of Blades	6
Warranty			
www.kichler.com/warranty			

ALSO IN THIS FAMILY



300241AVI



300241AVI7



300241WZC

You can see all products in this family by searching **Kichler.com**