KILLARK®

UGR Series 20A 250V Quick-Wire Acceptor Receptacle

By Killark Catalog # UGRO-20232QW

20A 250V Quick-Wire Acceptor Receptacle.



*Representative Image

Features

- Factory sealed chamber in UGR receptacle contains switch's arcing components.
- Spring loaded receptacle cover closes when plug is removed.
- Copper-free aluminum (less than 4/10 of 1%) alloy resists corrosion
- Electrostatically applied and baked powder epoxy/polyester finish
- ACCEPTOR® plugs conform to NEMAconfigurations, while it's "turn to engage" feature locks in plug and can be used to prevent accidental disengagement of critical equipment.
- Plugs for use with type S/SO/ST/STO heavy duty cord.

General

Material Aluminum, Copper Free (less

than 4/10 of 1%)

Number Of Poles 2

Receptacle Type Delayed Action

Series UGR

Type • Straight Blade

Straight Blade

UPC 783936125770

Electrical Ratings

Amperage Rating 20 A

Conductor Related

Number Of Wires 3

Certifications and Compliance

Hazardous Rating(s) • Class I, Divisions 1 & 2,

Groups C, D

• Class I, Zones 1 & 2, Groups

IIB, IIA

• Class II, Divisions 1 & 2,

Groups F, G

Class III, Divisions 1 & 2

Nema Rating 3, 7(C, D), 9(F, G)

Logistics

Factory Sealed Factory Sealed

Product Assets

Certifications - UGR/UGP Series UL Certification Customer Notices - Prop 65 Notice Installation Manuals - KIL_UGR,UGRQW Series Receptacles IOM_K1007

