



UGR Series 20A 125V Acceptor Receptacle Quick-Wire, 1/2" Dead End

By Killark
Catalog # [UGR1-20231QW](#)

20A 125V Acceptor Receptacle Quick-Wire, 1/2" Dead End.



*Representative Image

Features

- Factory sealed chamber in UGR receptacle contains switch's arcing components.
- Spring loaded receptacle cover closes when plug is removed.
- Copper-free aluminum (less than 4/10 of 1%) alloy resists corrosion
- Electrostatically applied and baked powder epoxy/polyester finish
- ACCEPTOR® plugs conform to NEMA configurations, while it's "turn to engage" feature locks in plug and can be used to prevent accidental disengagement of critical equipment.
- Plugs for use with type S/SO/ST/STO heavy duty cord.

General

Hub Pattern	Dead-End
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Number Of Poles	2
Receptacle Type	Delayed Action
Series	UGR
Type	<ul style="list-style-type: none">• Straight Blade• Straight Blade
UPC	783936125022

Dimensions

Hub Size	1/2"
----------	------

Electrical Ratings

Amperage Rating	20 A
-----------------	------

Conductor Related

Number Of Wires	3
-----------------	---

Certifications and Compliance

Hazardous Rating(s)	<ul style="list-style-type: none">• Class I, Divisions 1 & 2, Groups C, D• Class I, Zones 1 & 2, Groups IIB, IIA• Class II, Divisions 1 & 2, Groups F, G• Class III, Divisions 1 & 2
Nema Rating	3, 7(C, D), 9(F, G)

Logistics

Factory Sealed	Factory Sealed
----------------	----------------

Product Assets

[Certifications - UGR/UGP Series UL Certification](#)
[Customer Notices - Prop 65 Notice](#)
[Engineering Drawing - UGR Series Single Gang Dead End Engineering Drawing \(DWG\)](#)
[Sales Drawings - UGR Series Single Gang Dead End Sales Drawing \(PDF\)](#)



A proud member of the Hubbell Family.