



# UGR Series 15A 125V Acceptor Receptacle Quick-Wire, 3/4" Dead End

By Killark  
Catalog # [UGR2C-15231QW](#)

15A 125V Acceptor Receptacle Quick-Wire, 3/4" Dead End.



\*Representative Image

### Features

- Factory sealed chamber in UGR receptacle contains switch's arcing components.
- Spring loaded receptacle cover closes when plug is removed.
- Copper-free aluminum (less than 4/10 of 1%) alloy resists corrosion
- Electrostatically applied and baked powder epoxy/polyester finish
- ACCEPTOR® plugs conform to NEMA configurations, while it's "turn to engage" feature locks in plug and can be used to prevent accidental disengagement of critical equipment.
- Plugs for use with type S/SO/ST/STO heavy duty cord.

### General

Hub Pattern	Dead-End
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Number Of Poles	2
Receptacle Type	Delayed Action
Series	UGR
Type	<ul style="list-style-type: none"><li>• Straight Blade</li><li>• Straight Blade</li></ul>
UPC	783936125978

### Dimensions

Hub Size	3/4"
----------	------

### Electrical Ratings

Amperage Rating	15 A
-----------------	------

### Conductor Related

Number Of Wires	3
-----------------	---

### Certifications and Compliance

Hazardous Rating(s)	<ul style="list-style-type: none"><li>• Class I, Divisions 1 &amp; 2, Groups C, D</li><li>• Class I, Zones 1 &amp; 2, Groups IIB, IIA</li><li>• Class II, Divisions 1 &amp; 2, Groups F, G</li><li>• Class III, Divisions 1 &amp; 2</li></ul>
Nema Rating	3, 7(B, C, D), 9(F, G)

### Logistics

Factory Sealed	Factory Sealed
----------------	----------------

### Product Assets

[Customer Notices - Prop 65 Notice](#)  
[Engineering Drawing - UGR Series Single Gang Dead End Engineering Drawing \(DWG\)](#)  
[Sales Drawings - UGR Series Single Gang Dead End Sales Drawing \(PDF\)](#)



A proud member of the Hubbell Family.