



VUXBGG-1-200PX

By Killark
Catalog # [VUXBGG-1-200PX](#)

300W V Series Incandescent - Ceiling Fixture With Mounting Feet Using VBC Splice Box & VBA Adapter - 1/2" Hub with Guard - Unit Pack.



Features

- Electrostatically applied epoxy/polyester finish
- Modular design
- Hubs are threaded for attachment to conduit
- Set screws in pendant fixture
- Copper-free aluminum (less than .004%)

General

Finish Type	Peinture époxy en poudre
Lamp Type	Medium Base
Light Source	Incandescent
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Mounting Type	Ceiling
Optic Type	Glass Globe - Clear
Series	V Series
UPC	783936750255

Dimensions

Hub Size	1/2"
----------	------

Electrical Ratings

Frequency Rating	50/60 Hz
Voltage Rating	120-277 VAC
Wattage	300 W

Certifications and Compliance

Hazardous Rating(s)	• Class I, Division 2, Groups A, B, C, D • Class I, Zone 2, Groups IIC, IIB, IIA
---------------------	--

Product Assets

[Customer Notices - Prop 65 Notice](#)
[Installation Manuals - KIL_V-Series Incandescent Luminaires IOM_K1153](#)
[Photometry - KIL_Vxxxx-x-200](#)
[Photometry - KIL_Vxxxx-x-200-S](#)



A proud member of the Hubbell Family.