
PRODUCT SHEET

Kindorf® Angler® pipe and conduit clamp

Expanded line for more applications



Kindorf® Angler® pipe and conduit clamp



Easy bolt access

- Angler makes it simple to reach bolts with a screwdriver or power tool, even when clamps are installed side by side

Fast installation

- Keyhole-shaped opening enables bolt to be fed through strap without first being unthreaded

Convenient, one-piece design

- No disassembly
- No spare parts to lose or drop
- Easy to carry and store

Superior load performance

- One of the highest load ratings of any break-apart strap in the industry
- Integrated, rolled threading provides the load performance of a hex nut without the extra hardware

Universal series

- For EMT, IMC, rigid and standard pipe
- One versatile clamp fits snugly on a variety of conduit and pipe

Rigid series

- For rigid conduit and standard pipe
- Specialized clamp offers a superior, custom fit and an outstanding load rating

Galv-Krom® outperforms other finishes

- Gold color matches Kindorf strut systems and outperforms other finishes for corrosion protection, abrasion resistance and service life

Also available in SilverGalv® finish

- Versatile electrogalvanized silver color matches other pre-galvanized or green painted strut systems

Universal series

For EMT, IMC, rigid and standard pipe



Cat no.	Size (in.)	Strap thickness (ga.)	Design load (lbs.)	Install torque (in. lbs.)	Std. pkg. qty.
Galv-Krom finish					
C 109 1/2	½	14	400	40	100
C 109 3/4	¾	14	500	40	100
C 109 1	1	14	500	40	100
C 109 1 1/4	1¼	14	500	40	100
C 109 1 1/2	1½	12	800	60	50
C 109 2	2	12	800	60	50
C 109 2 1/2	2½	12	800	60	50
C 109 3	3	12	800	60	50
C 109 3 1/2	3½	11	1200	60	25
C 109 4	4	11	1200	60	25
SilverGalv finish					
C 109 1/2 EG	½	14	400	40	100
C 109 3/4 EG	¾	14	500	40	100
C 109 1 EG	1	14	500	40	100
C 109 1 1/4 EG	1¼	14	500	40	100
C 109 1 1/2 EG	1½	12	800	60	50
C 109 2 EG	2	12	800	60	50
C 109 2 1/2 EG	2½	12	800	60	50
C 109 3 EG	3	12	800	60	50
C 109 3 1/2 EG	3½	11	1200	60	25
C 109 4 EG	4	11	1200	60	25

Hex head size ⅜" for ½" to 1¼" sizes, ½" for 1½" to 4" sizes.

Material: stamped steel.

Pipe sizes 2½" to 4" utilize the same clamps for the rigid series and the universal series.

Rigid series

For rigid conduit and standard pipe



Cat no.	Size (in.)	Strap thickness (ga.)	Design load (lbs.)	Install torque (in. lbs.)	Std. pkg. qty.
Galv-Krom finish					
C 109R 1/2	½	14	600	40	100
C 109R 3/4	¾	14	600	40	100
C 109R 1	1	14	600	40	100
C 109R 1 1/4	1¼	14	600	40	100
C 109R 1 1/2	1½	12	800	60	50
C 109R 2	2	12	800	60	50
C 109 2 1/2	2½	12	800	60	50
C 109 3	3	12	800	60	50
C 109 3 1/2	3½	11	1200	60	25
C 109 4	4	11	1200	60	25
SilverGalv finish					
C 109R 1/2 EG	½	14	600	40	100
C 109R 3/4 EG	¾	14	600	40	100
C 109R 1 EG	1	14	600	40	100
C 109R 1 1/4 EG	1¼	14	600	40	100
C 109R 1 1/2 EG	1½	12	800	60	50
C 109R 2 EG	2	12	800	60	50
C 109 2 1/2 EG	2½	12	800	60	50
C 109 3 EG	3	12	800	60	50
C 109 3 1/2 EG	3½	11	1200	60	25
C 109 4 EG	4	11	1200	60	25

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB Inc.
Copyright© 2018 ABB
All rights reserved

ABB Installation Products Inc.
Electrification Products Division
860 Ridge Lake Blvd.
Memphis, TN 38120

tnb.abb.com

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB Inc. does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

77KK000099 12.2018