

# Cable Shears

with twin cutting edge

95  
1

- > for cutting copper and aluminum cables
- > not suitable for steel wire and hard drawn copper conductors
- > precision ground, hardened blades
- > clean and smooth cut without crushing and deformation
- > by dividing the cutting actions into initial cut (insulating sheath in the front cutting area) and final cut (conductor in the back cutting area), cables up to 25/32" (20 mm) dia. can be cut in one-hand operation
- > less effort required due to favorable lever ratio and optimized cutting-edge geometry
- > pinch guard prevents operators' fingers being pinched
- > adjustable bolted joint, self-locking
- > high-grade special tool steel; forged, oil-hardened



Initial cut: using the front cutting edge to cut the insulating sheath on larger cable diameters leaves an ergonomic handle opening width.



Final cut: after cutting the sheath in the front profile the conductors are cut in the rear area.



95 11 200  
PATENTED



95 12 200  
PATENTED



95 18 200 SBA  
1000 V ASTM PATENTED

The twin cutting edge allows a comfortable handle position in all cutting situations inside the specified cutting capacity.

| Product Number | Packaging | ↔<br>Inch<br>mm |  | Tool      | Handles  | Cutting capacities |                   | AWG | ⚖<br>lbs |
|----------------|-----------|-----------------|--|-----------|--|--------------------|-------------------|-----|----------|
|                |           |                 |  |           |  | ⊘ Inch<br>⊘ mm     | ⊘ mm <sup>2</sup> |     |          |
| 95 11 200      | X         | 8<br>200        |  | burnished | plastic coated                                   | 25/32<br>20        | 70                | 2/0 | 0.65     |
| 95 12 200      | X         | 8<br>200        |  | burnished | multi-component grips                            | 25/32<br>20        | 70                | 2/0 | 0.74     |
| 95 18 200 SBA  | X         | 8<br>200        |  | burnished | insulated, multi-component grips,<br>ASTM-tested | 25/32<br>20        | 70                | 2/0 | 0.75     |