

DN9c Multipin Plugs & Receptacles – 20A

UL/CSA Ratings

- **Voltage**
50 VAC or 480 VAC Max/130 VDC+
* For DC order 480V model.
Not CSA listed.
- **Amperage Rating**
20A Current Interrupting
- **Horsepower Ratings**

120V	1Ø	1/3 hp
240V	1Ø	1 hp
208V	3Ø	2 hp
240V	3Ø	3 hp
480V	3Ø	5 hp
- **Environmental Ratings**
IP54/IP55
- **Temperature Range**
Min -40°F/Max 140°F
See pg 253 for temps below -15°F.
- **Wiring Capacity**
Min 16 AWG Max 10 AWG
- **Certifications**
CSA 182.01

Receptacle (female)



Inlet (male)



! Don't forget to add installation accessories to your order

North American UL/CSA Configurations

Voltage	Polarity	Part # Poly	Part # Poly
50V	6P	17-14060	17-18060
50V	7P	17-14070	17-18070
50V	8P	17-14080	17-18080
50V	9P	17-14090	17-18090
480V	5P+G	17-14051	17-18051
480V	6P+G	17-14061	17-18061
480V	7P+G	17-14071	17-18071
480V	8P+G	17-14081	17-18081

For international configurations and ratings (IEC,CE) visit meltric.com/international-catalog or contact customer service at 800.433.7642.

Main Options



**Mushroom
Pawl**



Padlock Pawl

Receptacle Options

Suffix

Inlet Options

Suffix

Straight Insertion	Recept # - A188	Straight Insertion	Inlet # - A188
Self-Ejecting Connector Release	Recept # - 348-A188		
HP Watertightness (high pressure)	Recept # - HP		
Mushroom Pawl	Recept # - 375		
Locking Mushroom Pawl	Recept # - 845		
Padlock Pawl	Recept # - 843		
Padlockable Mushroom Pawl	Recept # - 375-843		
Closed Lid Configuration	Recept # - NC		



See pages 230-239 for detailed information on these options

Order Example: 50V DN9c with Closed Lid Configuration

DN9c Receptacle 9P = 17-14090-NC