

**Descriptors** 



## Catalog No. R055C010U

Description: 70A SURFACE MTRD 50/20GFCI

UPC No 784567205466

Home > Temporary Power > Temporary Power

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Descriptors	
Category	Temporary Power
Specifications	
Mounting	Surface
Heads	Surface
Metering	Ringless
Receptacles	14-50WR(BR54UWR) 5-20WR2GFCI
Feed	Underground
AIC	10,000
Amps	70.0 A
Cabinet Size	9 X 30U
Circuit Protection	Yes
Hub Provision	Yes
Installed Breaker	CB250 CB120
Load Center	LC33N1
Loop Feed	No
Phase	1
Unit Weight	25.0 lb
Volts	120/240
Classifications	
Stock Class Code	Non Stock
Approvals	
Certification	UL/CUL

midwestelectric.com Created on: 09/30/2024