



Catalog No. U010S010GRP

Description: 20GFCI/SWITCH SURFACE UNMTRD GREEN

UPC No 784567301496

Home > Power Outlets

Midwest Electric's Temporary Power and Power Outlets are a means of providing power required by various construction trades, residential sites, and mobile electrical applications. Temporary Power and Power Outlets offer one or more receptacles, with or without overcurrent protection, disconnecting, metering, and/or pedestal mounting functions, in a single enclosure of G-90 zinc-coated steel. The NEMA 3R rainproof enclosure is lockable and engineered to provide maximum protection against weather, vandalism, and normal field use.

Descriptors	
Category	Power Outlets
Specifications	
Mounting	Surface
Heads	1
Metering	Unmetered
Receptacles	5-20WR2GFCI & SWITCH
Feed	Overhead
AIC	10,000
Amps	20 A
Cabinet Size	5 in. W X 7 in. H
Circuit Protection	None
Hub Provision	No
Installed Breaker	None
Load Center	None
Loop Feed	No
Phase	1
Suitable for Service Equipment	No
Unit Weight	4.5 lb
Volts	120
Classifications	
Standard Package	1
Stock Class Code	Stock
Approvals	
Certification	UL/CUL

midwestelectric.com Created on: 07/22/2025