


Regular Bodied 303 Series Clear Cements



- ▶ Regular Bodied Clear Cement for PVC pipe and fittings up to 4" diameter for Sch. 40 pipe & up to 2" for Sch. 80 with interference fit
- ▶ Recommended application temperature 40°F to 110°F
- ▶ Sets up Quickly
- ▶ Low-Voc Compliant, Meets ASTM-D2564

Cat. No.	Size	Case Qty	Wt/Case
G30366S	1/4 Pt.	24	9
G30356S	1/2 Pt.	24	16
G30346S	1 Pt.	24	27
G30336S	1 Qt.	12	26
G30324	1 Gal.	6	52

Medium Bodied 404 Series Clear Cements



- ▶ Medium Bodied Clear Cement for PVC pipe and fittings up to 6" diameter for Sch. 40 and Sch. 80
- ▶ Recommended application temperature 40°F to 110°F
- ▶ Low-Voc Compliant, Meets ASTM-D2564

Cat. No.	Size	Case Qty	Wt/Case
G40466S	1/4 Pt.	24	9
G40456S	1/2 Pt.	24	16
G40446S	1 Pt.	24	27
G40436S	1 Qt.	12	26
G40424	1 Gal.	6	52

Medium Bodied 403 Series Gray Cements



- ▶ Medium Bodied Gray Cement for PVC pipe and fittings up to 6" diameter for Sch. 40 and Sch. 80 Conduits
- ▶ Recommended application temperature 40°F to 110°F
- ▶ Low-Voc Compliant, Meets ASTM-D2564

Cat. No.	Size	Case Qty	Wt/Case
G40366S	1/4 Pt.	24	9
G40356S	1/2 Pt.	24	16
G40346S	1 Pt.	24	27
G40336S	1 Qt.	12	26
G40324	1 Gal.	6	52

Polar-Weld 2600 Series - Fast Set - All Weather - Clear Cements



- ▶ Medium Bodied Clear Cement for PVC pipe and fittings up to 6" diameter for Sch. 40 and Sch. 80
- ▶ Formulated for fast initial set-up at temperatures down to -15°F to 110°F
- ▶ Low-Voc Compliant, Meets ASTM-D2564

Cat. No.	Size	Case Qty	Wt/Case
G2666S	1/4 Pt.	24	9
G2656S	1/2 Pt.	24	16
G2646S	1 Pt.	24	27
G2636S	1 Qt.	12	26
G2624	1 Gal.	6	52

Quick Set
Cold Weather

Plumb-Tite 2000 Series - Fast Set - Wet Application Cements



- ▶ Medium Bodied Blue Cement for PVC pipe and fittings up to 6" dia.
- ▶ Sch. 40 and Sch. 80
- ▶ Very Fast Setting Cement formulated for Wet Conditions and/or quick Pressurization and Fast Installation
- ▶ Fades to clear in sunlight
- ▶ Recommended application temperature 40° to 110°F
- ▶ Also for use on EMT Conduit
- ▶ Low-Voc Compliant, Meets ASTM-D2564

Cat. No.	Size	Case Qty	Wt/Case
G2066S	1/4 Pt.	24	9
G2056S	1/2 Pt.	24	16
G2046S	1 Pt.	24	27
G2036S	1 Qt.	12	26
G2024	1 Gal.	6	52

Quick Set
Wet Conditions