

# TORKALERT™

## Warning Lights

### Industrial Units



#### APPLICATIONS

- 1/2" conduit mounting. Full selection of dome colors. For outdoor use. All units must be mounted vertically with base at bottom.

#### FEATURES

- **All Purpose 360° Beacon:** Large parabolic reflector rotates around a 100 watt bulb. Long range beam. Use to indicate equipment malfunctions, security intrusion, etc..
- **Midi-Strobe:** Solid state circuitry in a low profile design. No moving parts means less Maintenance!.
- **Compact Rotating Beacon:** Light intensifying reflector rotates around a low current 25 watt bulb. Bayonet socket for easy lamp replacement. Ideal for restricted or dangerous areas.
- **Electronic Strobe:** High intensity strobe tube with inner fluted lens for maximum brilliance. No moving parts makes it immune to shock and vibration. Ideal for security alert.
- **Color:** Red (R), Amber (A), Clear (C) and Blue (B).



| CAT. NO.  | FIG. NO. | CERTIFICATION | TYPE                    | UPC CODE | DESCRIPTION                                                                                                                                                                                                     | INPUT VOLTAGE | AMPS |
|-----------|----------|---------------|-------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|------|
| TA47RN5   | 1        | —             | All Purpose 360° Beacon | 96061    | 90 FPM. Corrosion resistant/Outdoor use. Glass filled polypropylene housing Acrylic dome. Tamper resistant dome clamps. Nominal current draw 9 1/2"H x 8 1/2" diameter.                                         | 117VAC        | .9   |
| TA47AN5   | 1        | —             | All Purpose 360° Beacon | 96161    |                                                                                                                                                                                                                 | 117VAC        |      |
| TA93-2RN5 | 2        | —             | Midi-Strobe             | 99622    | 70-80 FPM. Solid state electronic circuitry. High output 3-4 watt, 3.6 joules Vertically mounted flash tube. Snap out socket base for 360° Fresnel dome optics. Nominal current draw 6 1/2"H x 5 1/8" diameter. | 117VAC        | .04  |
| TA93-2AN5 | 2        | —             | Midi-Strobe             | 97623    |                                                                                                                                                                                                                 |               |      |
| TA93-2CN5 | 2        | —             | Midi-Strobe             | 96968    |                                                                                                                                                                                                                 |               |      |
| TA93-2BN5 | 2        | —             | Midi-Strobe             | 97624    |                                                                                                                                                                                                                 |               |      |
| TA52RN5   | 3        | UL            | Compact Rotating Beacon | 96063    | 80-90 FP. 360° rotation. Dependable belt & turntable design. Acrylic dom. Nominal current draw 6 1/2"H x 55/8" diameter.                                                                                        | 117VAC        | .21  |
| TA52AN5   | 3        | UL            | Compact Rotating Beacon | 96163    |                                                                                                                                                                                                                 |               |      |
| TA52BN5   | 3        | UL            | Compact Rotating Beacon | 96263    |                                                                                                                                                                                                                 |               |      |
| TA94RN5   | 4        | —             | Electronic Strobe       | 97626    | 70-80 FPM. Solid state electronic circuitry High output 3-4 watt, 3.6 joules. Acrylic dome. Glass filled polypropylene housing. Suitable for outdoor use 9 1/2"H x 8 1/2" diameter.                             | 117VAC        | .04  |
| TA94AN5   | 4        | —             | Electronic Strobe       | 97627    |                                                                                                                                                                                                                 |               |      |
| TA94BN5   | 4        | —             | Electronic Strobe       | 97628    |                                                                                                                                                                                                                 |               |      |