

POOL & SPA

Digital Two-Speed Pump Timers

TPX Series



SPECIFICATIONS

- **Input Voltage:** 120 or 240VAC, 60Hz.
- **Output Voltage:**
 - TPX100(S): 12 & 13 VAC, 100 Watts max.
 - TPS300(S): 12, 13, & 14 VAC, 300 Watts max.
 - TPX600: 12, 13, & 14 VAC, 2 x 300 Watts max.
- **Color:** Grey or Stainless Steel.
- **Enclosure Size:**
 - TPX100(S) and TPX300(S) 7.2 H x 5.1 W x 4.2 D inches.
 - TPX600 10.4 H x 7.3 W x 4.2 D inches.

APPLICATIONS

- Swimming pool and spa lighting.
- Submersible fixtures.
- Landscape lighting.
- Fountain lighting.

FEATURES

- **Low Voltage:** Designed for the safe operation of 12 volt lighting loads including no niche fixtures.
- **Pool & Spa:** 100 watt unit for outdoor use only. 300 and 600 watt units for indoor or outdoor use.
- **Landscape Lighting:** 100 watt unit for outdoor use only. 300 and 600 watt units for indoor or outdoor use. All units for outdoor use only in Canada.
- **Safe Operation:** Full ground shield between primary and secondary.
- **Overload Protection:** Automatic resetting internal overload protection.



CAT. NO.	UPC CODE	INPUT SUPPLY 60Hz	OUTPUT CONTACTS
TPX100	94052	120VAC 1 AMP Max.	Painted Steel
TPX100S	94053	120VAC 1 AMP Max.	Stainless Steel
TPX300	94054	120VAC 3 AMP Max.	Painted Steel
TPX300S	94055	120VAC 3 AMP Max.	Stainless Steel
TPX600	94056	120VAC 2 x 3 AMP Max.	Painted Steel