

Project Name

Location

Prepared By



NUVO 67-121

EXIT/LIGHT DH - RED

Notes

(www) 03-12-2023 00:44:58

General

Status	Active
Fixture Type	Exit Sign
Finish	White
Wattage	2.8W
Lumen Output	150L
CCT (Kelvin)	5700K
Indoor or Outdoor Fixture	Indoor

Specifications

Technology	LED
CRI	70+
Voltage	120V/277V
Operating Temperature	+10C (+50F) to +40C (+104F)
Dimmable	Non-Dimmable
Lens Material	Polycarbonate (PC)
Surge Protection	Built-in surge protection - 3KV
Weight (lb.)	2.99
Material	Thermoplastic

Dimensions

Height (in.)	7.25
Width (in.)	19
Length (in.)	4

Compliance

Safety Listing	cULus - Certified; cULus - Listed
Location Rating	Damp
UL Application	EXIT Signs
Energy Star	No
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Fixture

Additional Information

Additional Information	Input Wattage: 2.8W; Output Wattage: 1.5W; Energy Used in Maintenance Mode: 2.8W
Specification Note	UL94V-0, Thermoplastic, 3.6V AA900mAh Ni-Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C; Letter Height: 6 in.; Letter Stroke: 0.75 in.; Path of Egress: 6 Ft
Includes	Mounting hardware and accessories
Warranty	2 Year Limited