

SKINDICHT® SM-M

SKINDICHT® SM-M, metric counter nuts for through-holes on thin-walled housing



Mechanical resistance



Good chemical resistance

Application range

Used in areas where a gland needs to be locked, or where thin-walled housing only allows through-holes.

Design

Metric connection thread according to DIN EN 60423

Basis for technical information DIN IEC 62444

Technical Data

Classification:

ETIM 5.0 Class-ID: EC000940

ETIM 5.0 Class-Description: Counter nut for cable gland

Material:

Nickel-plated brass

Temperature range:

-70°C to +100°C

Note

Photographs are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.



LAPP GROUP

PRODUCT INFORMATION

SKINDICHT® SM-M

Article number	Article designation / size	Thickness (mm)	SW mm	Outer Ø (mm)
SKINDICHT® SM-M				
52103000	M 12 x 1,5	3	15	16.5
52103010	M 16 x 1,5	3	19	20.9
52103020	M 20 x 1,5	3.5	24	26.4
52103030	M 25 x 1,5	4	30	33
52103040	M 32 x 1,5	4	36	39.6
52103050	M 40 x 1,5	5	46	50.6
52103060	M 50 x 1,5	5	60	65
52103070	M 63 x 1,5	5	70	77
52103071	M 75 x 1,5	8	85	95
52103072	M 90 x 2	10	102	114
52103073	M 110 x 2	12	124	135

Last Update (16.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16