

SILVYN® KCLICK-M

SILVYN® KCLICK-M - metric conduit gland for SILVYN® RILL



Variety of approval certifications



Temperature-resistant



Assembly time

Benefits

- Fast assembly
- Easy to disassemble
- Highly tensile
- High sealing performance
- Can be rotated

Application range

In combination with protective cable conduit:
SILVYN® RILL PA 6
SILVYN® RILL PA 12
Robot building
Rotating applications

Norm references / approvals

UL FILENUMBER E308201

Design

- Metric connection thread
- Basic body with inner seal
- Upper part with snap-in sleeve

Last Update (16.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SILVYN® KCLICK-M**Technical Data**

Classification:	ETIM 5.0 Class-ID: EC001176 ETIM 5.0 Class-Description: Gland for corrugated plastic hose
Colour delivered:	Grey RAL 7001 Black RAL 9005, UV-resistant
Material:	PA6
Protection rating:	IP 68 IP 69 according to DIN 40050 T.9
Temperature range:	-40°C to +115°C

Note

Photographs are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

**SILVYN® KLICK-M**

Article number	Metric size	SW mm	Total length mm	Thread length mm	Clear width (mm)	For conduit with outer Ø (mm)	Suitable for SILVYN® RILL
SILVYN® KLICK-M grey							
55501000	10 x 1.0	16	34.5	12	6	10	10
55501010	12 x 1.5	18	37	12	7	13	1 - 3
55501020	16 x 1.5/1	18	37	12	10	13	1 - 3
55501030	16 x 1.5/2	21	39	12	11	15.8	16
55501040	20 x 1.5/1	21	39	13	12	15.8	16
55501050	20 x 1.5/2	27	44.5	13	16	21.2	21
55501060	25 x 1.5	34	47	13	20.5	28.5	28
55501070	32 x 1.5	40	51	15	25.5	34.5	34
55501080	40 x 1.5	55	76	17	32	42.5	42
55501090	50 x 1.5	65	88	17	42.5	54.5	54
55500990	63 x 1.5	70	88	17	49	54.5	54
SILVYN® KLICK-M black							
55501005	10 x 1.0	16	34.5	12	6	10	10
55501015	12 x 1.5	18	37	12	7	13	1 - 3
55501025	16 x 1.5/1	18	37	12	10	13	1 - 3
55501035	16 x 1.5/2	21	39	12	11	15.8	16
55501045	20 x 1.5/1	21	39	13	12	15.8	16
55501055	20 x 1.5/2	27	44.5	13	16	21.2	21
55501065	25 x 1.5	34	47	13	20.5	28.5	28
55501075	32 x 1.5	40	51	15	25.5	34.5	34
55501085	40 x 1.5	55	76	17	32	42.5	42
55501095	50 x 1.5	65	88	17	42.5	54.5	54
55500995	63 x 1.5	70	88	17	49	54.5	54

Last Update (16.05.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03_16