

COMPUTER CABLES

Paired -Stranded -300 Volt
S-R PVC Insulation
Overall Aluminum Shield



CONSTRUCTION	
Conductor	- tinned copper
Insulation	- S-R PVC insulation with twisted pairs
Shield/Drain	- Overall Aluminum-polyester shield with tinned copper drain Wire
Jacket	- Chrome PVC

Applications:

- Allow balanced signal transmission which results in lower crosstalk through common mode rejection
- Permits higher data speeds than multi-conductor cables

Standards:

- UL Listed: 80C
- Voltage: 300 Volt

Part #	AWG	Conductors	Pairs	Stranding	Nom. O.D.	Nominal Capacitance A	Nominal Capacitance B	Lbs./M'
D52404	24		4	7x2 TC	.265"	30	50	36
D52405	24		5	7x2 TC	.289"	30	50	46
D52406	24		6	7x2 TC	.289"	30	50	52
D52407	24		7	7x2 TC	.294"	30	50	54
D52408	24		8	7x2 TC	.324"	30	50	62
D52409	24		9	7x2 TC	.334"	30	50	69
D52410	24		10	7x2 TC	.368"	30	50	75
D52415	24		15	7x2 TC	.417"	30	50	102
D52419	24		19	7x2 TC	.448"	30	50	122
D52425	24		25	7x2 TC	.503"	30	50	156
D52403	24	0	3	7x2 TC	.232"	30	50	30
D52401	24	2	1	7x2 TC	.156"	40	74	14
D52402	24	4	2	7x2 TC	.222"	30	50	30

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances

COLOR CODE CHART

Cond. #	Color
1	Black & Red
2	Black & White
3	Black & Green
4	Black & Blue
5	Black & Yellow
6	Black & Brown
7	Black & Orange
8	Red & White
9	Red & Green
10	Red & Blue
11	Red & Yellow
12	Red & Brown
13	Red & Orange
14	Green & White
15	Green & Blue
16	Green & Yellow
17	Green & Brown
18	Green & Orange
19	White & Blue
20	White & Yellow
21	White & Brown
22	White & Orange
23	Blue & Yellow
24	Blue & Brown
25	Blue & Orange