

Pass and Seymour Series 16 In-Line Connectors

Part No. PS20FBR



400A 600V, Cable Size #2 - 2/0, Female Cam-Type Plug, Green

Features & Benefits

Thermoplastic elastomer housing for outstanding impact and chemical Exceptional seal for maintaining NEMA Type 3R and resistance 4 integrity

Non-conductive retaining screw helps to insure no contact with live parts, along with providing stability to the fully assembled product

Heavy-duty hex set screws allow greater termination torque

Copper shim bundles wire strands to reduce "splaying."

Heavy-duty brass male and female contacts provide a superior and consistent means of conductivity

Copper wire provides quality strain relief

Specifications

| Gen | era | al I | nfo |
|-----|-----|------|--------------|
| Gen | era | al I | \mathbf{n} |

| Product Line | Pass & Seymour | Color | Red |
|--------------------|-----------------------|-------------------|------------|
| UPC Number | 785007308129 | Country Of Origin | Mexico |
| Application Sector | Commercial/Industrial | Standard | UL, cCSAus |

Technical Information

| Amperage | 400 A | Number of Poles | Single Pole |
|-----------|-------|-----------------|-------------|
| Wire Size | 2/0 | Voltage | 600.0 V |

Environmental Conditions

Operating Temperature: Maximum continuous

+75°C, minimum -40°C without impact:

Flammability UL94 V2: Enclosure: NEMA Type

3R and 4