



Pass and Seymour  
Series 16 In-Line Connectors, Orange  
Part No. PS20MBO



400A 600V M PLUG ORANGE #2-2/0

## Features & Benefits

Thermoplastic elastomer housing for outstanding impact and chemical resistance, as well as an exceptional seal for maintaining NEMA Type 3R and 4 integrity. Non-conductive retaining screw helps to insure no contact with live parts, along with providing stability to the fully assembled product. Heavy-duty brass male and female contacts provide a superior and consistent means of conductivity. Heavy-duty hex set screws allow greater termination torque. Copper wire provides quality strain relief. Copper shim bundles wire strands to reduce "splaying."

## Specifications

### General Info

|                    |                       |                   |            |
|--------------------|-----------------------|-------------------|------------|
| Product Line       | Pass & Seymour        | Color             | Orange     |
| UPC Number         | 785007422702          | Country Of Origin | Mexico     |
| Application Sector | Commercial/Industrial | Standard          | UL, cCSAus |

### Technical Information

|                          |                                                                                                                                       |                 |             |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------|-----------------|-------------|
| Amperage                 | 400 A                                                                                                                                 | Number of Poles | Single Pole |
| Wire Size                | 2/0                                                                                                                                   | Voltage         | 600.0 V     |
| Environmental Conditions | Operating Temperature: Maximum continuous +75°C, minimum -40°C without impact:<br>Flammability UL94 V2: Enclosure: NEMA Type 3R and 4 |                 |             |