



radiant Collection  
radiant® Momentary Contact Switch  
Part No. TM870STMLACC6



The radiant® Momentary Contact Switch is perfect anywhere you need the safety of a switch that is only on when held in the "on" position. Made exclusively for use with screwless Wall Plates from the radiant® Collection, sold separately.

## Features & Benefits

- Part of the radiant® collection. High-impact resistant thermoplastic construction
- Narrow back body leaves more room for wires in the box. Extra-long, through-body strap eliminates floating installations and imperfect applications
- Smooth, quiet paddle action Complete the look with a sleek, screwless radiant® Wall Plate, and coordinate with other designer switches and outlets available from the radiant® Collection.

## Specifications

### General Info

|                    |                         |                    |                       |
|--------------------|-------------------------|--------------------|-----------------------|
| Product Line       | Pass & Seymour          | Color              | Light Almond          |
| UPC Number         | 785007043679            | Country Of Origin  | Mexico                |
| Switch Type        | Paddle                  | Number of Switches | 1                     |
| Application Sector | Residential             | Standard           | CSA Listed, UL Listed |
| Warranty Type      | 1-Year Limited Warranty |                    |                       |

### Dimensions

|                   |         |                  |         |
|-------------------|---------|------------------|---------|
| Product Width US  | 1.43 in | Product Depth US | 1.27 in |
| Product Height US | 4.19 in |                  |         |

### Listing Agencies / 3rd Party Agencies

|              |     |
|--------------|-----|
| cULus Listed | Yes |
|--------------|-----|

Additional Information

|                               |     |
|-------------------------------|-----|
| Product Environmental Profile | Yes |
|-------------------------------|-----|

Technical Information

|                  |             |                          |         |
|------------------|-------------|--------------------------|---------|
| Operating Cycles | 50000       | Contact Rating           | 120V    |
| Number of Gangs  | 1           | Amperage                 | 15 A    |
| Number of Poles  | Single Pole | Mounting Type            | Box     |
| Voltage          | 120.0 V     | Environmental Conditions | UL94 V2 |