



Color: Brushed nickel

Weight: 3.5 lbs

Project:

Type:

Prepared By:

Date:

Driver Info

LED Info

| | | | |
|-------------|---------------------------|----------------|---------------------------|
| Type | Constant Current, Class 2 | Watts | 38W |
| 120V | 0.35A | Color Temp | 2700/3000/3500/4000/5000K |
| 208V | N/A | Color Accuracy | >90 CRI |
| 240V | N/A | L70 Lifespan | 50,000 Hours |
| 277V | N/A | Lumens | 3,200 lm |
| Input Watts | 38W | Efficacy | 85 |

Technical Specifications

Performance

Description:

The ENCHANT vanity family is a sleek & traditional fixture perfect for single or multi-family projects

Wattage Equivalency:

320W Incandescent

Input Wattage:

38W

Lumens:

3,200lm

Efficacy:

85lm/W

L70 Lifespan:

50,000-Hour LED lifespan based on IES LM-70 results

Driver:

Linear

Electrical

THD:

<50%

Power Factor:

>0.9

Dimmable:

Yes, dimmable down to 10% on compatible TRIAC/ELV dimming systems. See Dimmer Compatibility List.

Input Voltage:

120V

Operating Frequency:

60 Hz

Input Current @ 120V (mA):

352mA

Operating Temperature:

-4°F to 104°F (-20°C to 40°C)

Flicker:

<30%

LED Characteristics

Beam Angle:

140°

Color Temperature:

Field adjustable via dip switch
2700/3000/3500/4000/5000K

R9 Value:

High color performance with R9 greater than 50

Color Consistency:

<7-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Color Stability:

LED color temperature is warrantied to shift no more than 200K in color temperature over a 5-year period

Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Installation

Mounting:

Flush mount

Construction

Length:

36"

Shape:

Linear

Finish:

Brushed Nickel

Enclosure Material:

Polycarbonate/Metal

Technical Specifications (continued)**Lens Finish:**

Frosted

Lens:

Polycarbonate light diffuser distributes light evenly and smoothly for general lighting applications

Compliance**ETL Listed:**

This product has been tested by Intertek and found in compliance with accepted national standards.

Environment:

Suitable for use indoors in dry and damp environments.

IC Rated:

No

Air Tight:

No

Energy Star Approved:

No

DLC Listed:

No

Certification Model Number:

V007(ENCT-36BN)

California Title 20 Compliant:

No

California Title 24 JA8 Compliant:

Can be used to conform with the requirements of California Title 24 Part 6

California Energy Commission (CEC) Status:

Lawful for Sales in California

NSF Listed:

No

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

RoHS:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15 of the FCC Rules


Other**Compatible Accessories:**

None

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Dimensions



Features

- Steel housing with a shatter-resistant polycarbonate lens
- Black/Brushed Nickel finishes for modern style
- 5CCT Selectable 2700/3000/3500/4000/5000K
- 120V driver with TRIAC/ELV dimming down to 10%_
- Damp rated, Title 24 Compliant, 50,000 hrs, 5-year no compromise warranty

Ordering Matrix

| Family | Size/Wattage | Shape | CRI/Color Temp | Driver | Finish |
|---|--------------|-------|----------------|--------|--------|
| ENCT | 36 | | | | BN |
| Blank = 10" Sconce, 20W Blank = Round Blank = 90 CRI, 2700/3000/3500/4000/5000K CCT Adjustable Blank = 120V, TRIAC/ELV BN = Brushed Nickel | | | | | |
| 24 = 24", 28W 36 = 36", 38W 48 = 48", 50W | | | | | |