




Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Type	Constant Current	Watts	36W
120V	0.30A	Color	3000/3500/4000/5000K
208V	0.18A	Temp	
240V	0.15A	Color Accuracy	84 CRI
277V	0.13A	L70 Lifespan	100,000 Hours
Input Watts	23-48.6W	Lumens	2888-6603 lm
		Efficacy	125.6-135.9 lm/W

Technical Specifications

Field Adjustability

Field Adjustable:

Field Adjustable Light Output:
48W/36W/24W (factory default 36W)
Color temperature (selectable by 5000K, 4000K, 3500K and 3000K)

Compliance

UL Listed:

Suitable for damp locations

IESNA LM-79 & LM-80 Testing:

RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

Trade Agreements Act Compliant:

This product is a product of Cambodia and a "designated country" end product that complies with the Trade Agreements Act

DLC Listed:

This product family is listed with the DesignLights Consortium (DLC). Individual SKUs within this family may carry either a DLC Standard or DLC Premium qualification. Please refer to the individual product specification sheet or the DLC Qualified Products List (QPL) at designlights.org to confirm the qualification status of a specific SKU prior to specification or purchase.

Electrical

Driver:

24W: Constant Current, Class 2, 120-277V, 50/60Hz, 120V: 0.20A, 208V: 0.12A, 240V: 0.10A, 277V: 0.09A
36W: Constant Current, Class 2, 120-277V, 50/60Hz, 120V: 0.30A, 208V: 0.18A, 240V: 0.15A, 277V: 0.13A
48W: Constant Current, Class 2, 120-277V, 50/60Hz, 120V: 0.40A, 208V: 0.23A, 240V: 0.20A, 277V: 0.18A

Dimming Driver:

Driver includes dimming control wiring for 0-10V dimming systems. Requires separate 0-10V DC dimming circuit. Dims down to 5%.

THD:

6.6% at 120V, 11.4% at 277V

Power Factor:

99.6% at 120V, 96.9% at 277V

Surge Protection:

1-2 kV

Performance

Lifespan:

100,000-Hour LED lifespan based on IESIm-80 results and TM-21 calculations

Wattage Equivalency:

24W: Replaces up to (1) F32T8
36W: Replaces up to (2) F32T8
48W: Replaces up to (2) F32T8

LED Characteristics

LEDs:

Long-life, high-efficiency, surface-mount LEDs

Color Consistency:

4-step MacAdam Ellipse binning to achieve consistent fixture-to-fixture color

Color Uniformity:

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting (SSL) Products, ANSI C78.377-2017.

Construction

Cold Weather Starting:

The minimum starting temperature is -4°F (-20°C)

Maximum Ambient Temperature:

Suitable for use in up to 131°F (55°C)

Housing:

Cold Rolled Carbon Steel Sheets and Strip (SPCC)

Technical Specifications (continued)

Lens:
Diffused Polymethyl Methacrylate (PMMA)

Finish:
Formulated for high durability and long-lasting color

Green Technology:
Mercury and UV free. RoHS-compliant components.

Installation

Mounting:
Comes standard with two mounting accessories:
aircraft cable for secure, suspended mounts and a
stainless bracket for easy mounting to junction
boxes. Power cord and canopy cover included.


Other

Lighting Pattern:
70% downlight, 30% uplight

Accessories:
Fixture to fixture connector: [TOMO CONNECT](#)

5-Year, No-Compromise Warranty:
RAB warrants that our LED products will be free from
defects in materials and workmanship for a period of
five (5) years from the date of delivery to the end
user, including coverage of light output, color
stability, driver performance and fixture finish. RAB's
warranty is subject to all terms and conditions found
at [rablighting.com/warranty](#).

Dimensions



Features

- 0-10V dimming
- 100,000-Hour LED lifespan
- 5-Year, No-Compromise Warranty

Ordering Matrix

Family		Length (Wattage)	Color Temp	Finish	Driver	Controls	Battery Backup
TOMO	-	4					
		2 = 2' (24/18/12W) 4 = 4' (48/36/24W) 8 = 8' (96/72/48W)	Blank = 3000/3500/4000/5000K CCT Adjustable	Blank = White	Blank = 120-277V, 0-10V Dimming	Blank = No Option /PIR = Passive Infrared Occupancy Sensor /LC = Lightcloud /LCS = Lightcloud Sensor /LCB = Lightcloud Blue /LCBS = Lightcloud Blue w/PIR sensor /LCBS/MVS = Lightcloud Blue w/MVS sensor	Blank = None /E = Battery Backup

¹ *Available only for 4' and 8'