

Rittal – The System.

Faster – better – everywhere.

► **TopTherm Blue e Wall-Mounted Cooling Unit, UL Type 3R/4 Total cooling output 0.50 – 2.50 kW - 3303518**

Date : Jul 18 , 2019

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm Blue e Wall-Mounted Cooling Unit, UL Type 3R/4 Total cooling output 0.50 – 2.50 kW - 3303518

created: 07.18.2019 build on <https://www.rittal.us/>



Product Description

Total cooling output to DIN EN 14511

L 35 L 35 at 60 Hz: 0.55 kW

L 35 L 50 at 60 Hz: 0.32 kW

Air throughput (unimpeded air flow)

External circuit: 345 m³/h

Internal circuit: 280 m³/h

Rated operating voltage

115V 1~ 60Hz

Rated current (max)

5.7 A

Start-up current (max)

11.5 A

Miniature circuit-breaker/fuse

10A

Temperature range

Ambient temperature range: -20°C...+50°C

Storage: -40°C...+70°C

Setting range: +20°C...+50°C

Dimensions

Height: 620 mm

Width: 285 mm

Depth: 298 mm

Build depth

350 mm

Protection category IP to IEC 60 529

External circuit IP 34

Innenkreislauf IP 56

Protection category NEMA:

NEMA 4

NEMA 3R

	NEMA 12
Rated Power Pel	L 35 L 35 at 60 Hz: 0.42 kW L 35 L 50 at 60 Hz: 0.48 kW
Temperature control	e-Comfort Controller (factory setting +35°C)
Weight/packaging unit	25 kg
Refrigerant-cooling medium	Refrigerant: R134a Quantity: 170 g Global Warming Potential (GWP): 1430 CO ₂ equivalent (CO ₂ e): 0.24 t
Supply includes	Drilling template Fasteners Nano-coated condenser Wired ready for connection (plug-in terminal strip)
Note on Model No.	without integral condensate evaporation
Packaging unit	1 pc(s).
EAN	4028177943681
Customs tariff number	84158200
ETIM 6.0	EC000855
ETIM 5.0	EC000855
eCl@ss 8.0/8.1	27180704
eCl@ss 7.0/7.1	27180704
eCl@ss 6.0/6.1	27180704
eCl@ss 5.1/5.1.4	27180704