

Rittal – The System.

Faster – better – everywhere.



SE 5845.600

VX SE free-standing enclosure system

Stan: 2023-04-13 (Źródło: rittal.com/ca-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SE 5845.600 - VX SE free-standing enclosure system

Individual carbon steel enclosure with stable enclosure body, two integrated mounting levels, screw-fastened rear panel and door. Roof and sides from a single piece with roll-formed frame. Fully compatible with the VX25 baying system. Improves efficiency as side panels do not have to be mounted, and large enclosure widths replace small bayed suites.

Cechy

Model No.	SE 5845.600
Material	Housing: Carbon steel, 1.5 mm Door: Carbon steel, 2.0 mm Rear wall: carbon steel, 1.5 mm Base plates: Carbon steel, 1.5 mm Mounting plate: Carbon steel, 3.0 mm
Surface finish	Housing, door and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Mounting plate and base plates: Zinc-plated
Color	RAL 7035
Supply includes	Housing, solid top and sides Door(s) Right-hand door catch on single-door enclosures may be swapped to the left Mounting plate Base Plates Rear panel, detachable Lock: 3 mm double-bit 2 punched rails, 18 x 39 mm Rear wall, one-piece
Dimensions	Width: 1,200 mm Height: 2,000 mm Depth: 600 mm
Dimensions of mounting plate (W x H)	1,099 mm x 1,896 mm
Protection category IP to EN 60529	IP 55

Cechy

Protection category NEMA	NEMA 12
Type rating according to UL 50E	Type 1, 2, 3, 3R, 12
IK code	IK10
Number of doors	2
Lock	No. of locks: 2
Base material	Carbon steel
Packaging unit	1 pc(s).
Weight/packaging unit	206 kg
Copper weight (kg per piece)	0
EAN	4028177959231
ETIM 7.0	EC000261
ECLASS 8.0	27180101

Aprobaty

Aprobaty	GOST UL + C-UL (listed)
Certyfikaty	Surface finish Protection category
Wyjaśnienia	Declaration of conformity Declaration of conformity UK