

### **PVC Coated Elbows**

# 1-1/2X90 PVC COATED STANDARD ELBOW





 Catalog Number
 PRHELB-1-1/2X90

 UPC
 784011200320

## **Description**

Factory-bent PVC coated elbows are more accurate, quicker to install and more economical because they eliminate field bending time and waste of material. Electrical continuity is maintained across assembled joints.

### **Application**

 Factory-bent for accurate, quicker to install and eliminates costly field bending and waste of material

### **Features**

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 12 trade sizes from 1/2" through 6"
- Available in standard sizes 90°, 60°, 45°, 30° bends
- Color-coded thread protector caps for quick identification of conduit size

# Tangent External Diameter Offset Padii

### **General Information**

Trade Size	1-1/2
Material	STEEL
Material	STEEL
Exterior Finish	A nominal .040 inch (40 mil) gray PVC coating
Interior Finish	A nominal .002 inch (2 mil) red urethane
Thread Finish	A red urethane coating over steel
Thread Protector Color	Black

### **Dimensions**

Diameter - External (Inches) 1.98



Diameter - Internal (Inches)	1.624
Metric Size Designators	41
Nipple Length (Inches)	19-3/4
Offset D (Inches)	10.635
Offset E (Inches)	11.625
Offset F (Inches)	12.615
Radius A (Inches)	7.26
Radius B - Standard (Inches)	8.25
Radius C (Inches)	9.24
Tangent (Inches)	3.375



### **Standards**

CSA Certified	C22.2 No. 45
UL6	E2314

# **Technical Specification Documents**

Specification Guide (1995 Master)	AVAILABLE ON WEBSITE
Specification Guide (2004 Master)	AVAILABLE ON WEBSITE
Installer Certification and Tools	AVAILABLE ON WEBSITE
Chemical Resistance Charts	AVAILABLE ON WEBSITE
Performance Specifications	AVAILABLE ON WEBSITE

### **Technical Information**

Fitting Configuration	90
Fitting Type	STANDARD RADIUS ELBOW
Product Category	ELBOW
Product Family	PVC Coated Elbows

### **Notes**

- Both PVC and zinc coatings have been investigated as primary protection against corrosion.
- Restricted for use with threaded fittings only.