# **Hazardous location fitting**

# **LBY Type Service Entrance Elbows**

# 1 INCH LBY SERVICE ENTRANCE ELBOW



**Catalog Number** PRLBY35 **UPC** 784011208265

## **Description**

PVC coated LBY type elbows are used as service entrance elbows between service entrance and vertical weatherhead conduit runs, to change direction of a conduit run 90Åö when space is limited, and for pull outlets.

## **Additional Product Description**

May be used for general service or hazardous locations.

### **Application**

 Used as service entrance elbows between service entrance and vertical weatherhead conduit runs, to change direction of a conduit run 90 degree when space is limited, and for pull outlets

#### **Features**


- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 5 trade sizes from 1/2" through 1-1/2"
- Sealing sleeves on all conduit openings
- Molded PVC gasket seals fitting cover to body

#### **General Information**

Trade Size	1
Material	FERROUS METAL
Material	FERROUS METAL
Exterior Finish	A nominal .040 inch (40 mil) gray PVC coating
Interior Finish	A nominal .002 inch (2 mil) red urethane

#### **Dimensions**







# Hazardous location fitting

Dimension A (Inches)	3.25
Dimension B (Inches)	2.58
Nominal Weight (Pounds)	1.7

#### **Standards**

NEC/CEC	Class II, Division 2, Groups F, G
NEC/CEC	Class I, Division 1 & 2, Groups C, D
NEC/CEC	Class II, Division 1, Groups E, F, G
NEC/CEC	Class III

# **Technical Specification Documents**

Specification Guide (1995 Master)	AVAILABLE ON WEBSITE
Specification Guide (2004 Master)	AVAILABLE ON WEBSITE
Installer Certification and Tools	AVAILABLE ON WEBSITE
Chemical Resistance Charts	AVAILABLE ON WEBSITE
Performance Specifications	AVAILABLE ON WEBSITE

#### **Technical Information**

Feed Type	Feed Thru
Fitting Type	SERVICE ENTRANCE ELBOW
Product Category	HAZARDOUS LOCATION FITTING
Product Family	LBY Type Service Entrance Elbows
Rating	Hazardous Location

#### **Notes**

• May be used for general service or hazardous locations.

