

Conduit Unions UNF & UNY Unions

1/2 INCH FEMALE-TO-FEMALE (F/F) ALUMINUM UNF UNION



Catalog Number	PRUNF105SA
UPC	784011219261

Description

PVC coated UNF unions are used to connect conduit to conduit or to allow for future changes to the conduit system. Female threads are provided at each end.

Application

- Applicable for Hazardous Locations

Features

- 40 mil gray PVC exterior coating
- 2 mil red urethane interior coating
- 13 trade sizes from 1/2" through 6"
- Sealing sleeves on all conduit openings
- Molded PVC gasket seals fitting

General Information


Trade Size	1/2
Material	ALUMINUM
Material	ALUMINUM
Exterior Finish	A nominal .040 inch (40 mil) gray PVC coating
Interior Finish	A nominal .002 inch (2 mil) red urethane

Dimensions

Length (Inches)	1.81
Max Diameter (Inches)	2

Standards

CSA	C22.2 No. 30
NEC/CEC	Class II, Division 2, Groups F, G
NEC/CEC	Class III
NEC/CEC	Class II, Division 1, Groups E, F, G
NEC/CEC	Class I, Division 1 & 2, Groups A, B, C, D
UL 1203	E476062



Technical Specification Documents

Specification Guide (1995 Master)	AVAILABLE ON WEBSITE
Specification Guide (2004 Master)	AVAILABLE ON WEBSITE
Installer Certification and Tools	AVAILABLE ON WEBSITE
Chemical Resistance Charts	AVAILABLE ON WEBSITE
Performance Specifications	AVAILABLE ON WEBSITE

Technical Information

Fitting Configuration	F/F
Fitting Type	UNION
Product Category	HAZARDOUS LOCATION FITTING
Product Family	Conduit Unions UNF & UNY Unions
Rating	Hazardous Location