

Product data sheet

Specifications



APC NetShelter Basic Rack PDU, 1U, 30A, 120V, 10 NEMA 5-20 outlets

AP9560

Product availability: Stock - Normally stocked in distribution facility

Overview

| | |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

Main

| | |
|---------------------------|---------------------------------------|
| Color | Black |
| Product or Component Type | PDU |
| PDU Type | Basic |
| Cord length | 12 ft (3.7 m) |
| Number of cables | 1 |
| Provided Equipment | User Manual Rack Mounting brackets |

Complementary

| | |
|--------------------------|---------------------|
| Input Voltage | 100 V 120 V |
| Height | 1.73 in (4.4 cm) |
| Width | 17.60 in (44.7 cm) |
| Output Voltage | 120 V |
| Depth | 2.24 in (5.7 cm) |
| Net Weight | 5.5 lb(US) (2.5 kg) |
| Mounting Location | Front Rear |
| Mounting preference | No preference |
| Input Plug Type | NEMA L5-30P |
| Mounting Mode | Rack-mounted |
| Rack units | 1U |
| Mounting position | Horizontal |
| Line Rated Current | 24 A |
| Acceptable Input Voltage | 90...132 V |
| Max line current | 24 A |
| Input current limits | 30 A |
| Load Capacity | 2880 VA |
| Input Frequency | 50/60 Hz |
| Outlet type and quantity | 10 NEMA 5-20R |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

| | |
|---------------------------------------|----------------------------|
| Product Certifications | cUL Listed UL Listed |
| Standards | UL 60950 |
| Ambient Air Temperature for Operation | 5...113 °F (-15...45 °C) |
| Relative Humidity | 0...95 % |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Storage | -13...149 °F (-25...65 °C) |
| Storage Relative Humidity | 0...95 % |
| Storage altitude | 0...50000 ft (0...15240 m) |

Ordering and shipping details

| | |
|-------------------|---------------------------|
| Category | 11309-APC RESALE PRODUCTS |
| Discount Schedule | APC1 |
| GTIN | 731304192930 |
| Returnability | No |
| Country of origin | IN |

Packing Units

| | |
|------------------------|-----------------------|
| Unit Type of Package 1 | PCE |
| Nbr. of units in pkg. | 1 |
| Package 1 Height | 5.98 in (15.2 cm) |
| Package 1 Width | 6.97 in (17.7 cm) |
| Package 1 Length | 19.13 in (48.6 cm) |
| Package weight(Lbs) | 8.02 lb(US) (3.64 kg) |

Contractual warranty


| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|

Environmental Data


Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.


[Environmental Data explained >](#)

[How we assess product sustainability >](#)

|  Environmental footprint | |
|---|---|
| Carbon footprint (kg CO2 eq, Total Life cycle) | 64 |
| Environmental Disclosure | Product Environmental Profile |

Use Better

|  Materials and Substances | |
|--|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant |
| REACH Regulation | REACH Declaration |
| Halogen content performance | Product contains halogen above thresholds |

|  Energy efficiency | |
|---|--------------------------|
| Optimized Energy Efficiency | Energy efficient product |

Use Again


|  Repack and remanufacture | |
|--|---|
| Circularity Profile | End of Life Information |
| Take-back | Yes |

Image of product / Alternate images

Alternative



