

# standard auxiliary contact, ComPact NSXm, circuit breaker status OF/ SD, 1 changeover contact type

LV426950

Product availability: Stock - Normally stocked in distribution facility

### Main

Product or Component Type	Auxiliary contact	
Device short name	SD OF	
Device Application	Breaker status monitoring	
Range compatibility	PowerPact PowerPact B ComPact ComPact NSXm	
Signal contacts composition	1 NO/NC	

# **Complementary**

Overload	
Short-circuit	
ON/OFF indication for open/close	
Trip indicator for relay trip indicator	
The indicator for relay trip indicator	
Standard	
Clip-on	
al 5A	
AC-12: 5 A at 24 V AC 50/60 Hz	
AC-12: 5 A at 48 V AC 50/60 Hz	
AC-12: 5 A at 110127 V AC 50/60 Hz	
AC-12: 5 A at 220/240 V AC 50/60 Hz	
AC-12: 5 A at 380/440 V AC 50/60 Hz	
AC-12: 5 A at 660/690 V AC 50/60 Hz	
AC-15: 5 A at 24 V AC 50/60 Hz	
AC-15: 5 A at 48 V AC 50/60 Hz	
AC-15: 4 A at 110127 V AC 50/60 Hz	
AC-15: 3 A at 220/240 V AC 50/60 Hz	
AC-15: 2.5 A at 380/440 V AC 50/60 Hz	
AC-15: 0.1 A at 660/690 V AC 50/60 Hz	
DC-12: 5 A at 24 V DC 50/60 Hz	
DC-12: 2.5 A at 48 V DC 50/60 Hz	
DC-12: 0.6 A at 110 V DC 50/60 Hz	
DC-12: 0.3 A at 250 V DC	
DC-13: 2.5 A at 24 V DC	
DC-13: 1.2 A at 48 V DC	
DC-13: 0.35 A at 110 V DC	
DC-13: 0.05 A at 250 V DC	
DC-14: 1 A at 24 V DC	
DC-14: 0.2 A at 48 V DC	
DC-14: 0.05 A at 110 V DC	
DC-14: 0.03 A at 250 V DC	
2 mA 17 V DC	
spring	
0.3 in (8 mm) for front connection	

# Ordering and shipping details

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Category	US10DE201136	
Discount Schedule	0DE2	
GTIN	3606485444215	
Returnability	Yes	
Country of origin	CN	

# **Packing Units**

Unit Type of Package 1	PCE	
Nbr. of units in pkg.	1	
Package 1 Height	0.47 in (1.200 cm)	
Package 1 Width	2.95 in (7.500 cm)	
Package 1 Length	4.13 in (10.500 cm)	
Package weight(Lbs)	0.882 oz (25.000 g)	
Unit Type of Package 2	BB1	
Number of Units in Package 2	10	
Package 2 Height	1.97 in (5.000 cm)	
Package 2 Width	5.51 in (14.000 cm)	
Package 2 Length	9.84 in (25.000 cm)	
Package 2 Weight	9.065 oz (257.000 g)	
Unit Type of Package 3	S03	
Number of Units in Package 3	220	
Package 3 Height	11.81 in (30.000 cm)	
Package 3 Width	11.81 in (30.000 cm)	
Package 3 Length	15.75 in (40.000 cm)	
Package 3 Weight	13.889 lb(US) (6.300 kg)	



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint		
Carbon footprint (kg CO2 eq, Total Life cycle)	2	
Environmental Disclosure	Product Environmental Profile	

### **Use Better**

Materials and Substances	
Recycled metal content at CR level	0
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Offer Marketing Illustration

#### **Product benefits / Features**



## Offer Marketing Illustration

#### **Product benefits / Features**



## Offer Marketing Illustration

#### **Product benefits / Features**

