

communication module EtherNet IP Modbus TCP, 10 or 100Mbps, 2 x RJ45 connectors

VW3A3720

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Altivar	
Product or Component Type	Communication module	
Complementary		
Range compatibility	Altivar Process ATV600 Altivar Process Modular	
Communication Port Protocol	Modbus TCP EtherNet/IP	
Electrical connection	2 connectors RJ45, Ethernet IP/Modbus TCP	
Transmission Rate	10/100 Mbps	
Exchange mode	Half duplex and full duplex	
Communication service	SNMP agent Ethernet IP Modbus TCP server Ethernet IP/Modbus TCP Ethernet/IP adapter Ethernet IP RSTP support Ethernet IP FTP Ethernet IP ODVA AC drive and CiA 402 profile Ethernet IP/Modbus TCP Auto-MDIX Ethernet IP/Modbus TCP 32 parameters IN - 32 parameters OUT implicit messaging Ethernet IP/Modbus TCP FDR Ethernet IP/Modbus TCP	
Communication Network Type	IPv6 (internet protocol)	
Topology	Daisy chain	
Time synchronisation protocol	SNTP	
Web server	Embedded HTTP server	
Web services Save/restore drive configuration Drive setting and diagnostic Energy monitoring Widgets (ID, control, data table, diagnostic, charts) Upgrade drive firmware Customizable home page Drive monitor Pump function setting and monitoring Ethernet setting and diagnostic		
Display type	1 LED MS (Module Status) 1 LED NS (Network Status) 1 LED TX/RX (Transmit/Receive port 1) 1 LED TX/RX (Transmit/Receive port 2)	
Bus profile	CIP AC Drive CiA 402	
Net Weight	0.4 lb(US) (0.2 kg)	

Environment

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

ODVA Achilles level 2

Ordering and shipping details

Category	US1CP4E22276	
Discount Schedule	CP4E	
GTIN	3606480702549	
Returnability	Yes	
Country of origin	ID	

Packing Units

Unit Type of Package 1	PCE	
Nbr. of units in pkg.	1	
Package 1 Height	2.64 in (6.700 cm)	
Package 1 Width	5.12 in (13.000 cm)	
Package 1 Length	7.40 in (18.800 cm)	
Package weight(Lbs)	5.608 oz (159.000 g)	
Unit Type of Package 2	S03	
Number of Units in Package 2	16	
Package 2 Height	11.81 in (30.000 cm)	
Package 2 Width	11.81 in (30.000 cm)	
Package 2 Length	15.75 in (40.000 cm)	
Package 2 Weight	7.253 lb(US) (3.290 kg)	



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	4
Environmental Disclosure	Product Environmental Profile

Use Better

⊗ Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	Eabe1c38-4fea-4053-a04b-f026433c8b42
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No