1.5S1F

Transformer, dry type, encapsulated, 1.5kVA, 1 phase, 240x480V primary, 120/240V secondary, 8A, 115C rise





Main		
Product or Component Type	Dry Sealed Transformer	
Primary to Secondary Voltage	240 x 480 V 120/240 V	
Full Capacity Taps	0	

Complementary

Enclosure Code	8A	
Phase	1 phase	
Power Rating	1.5 kVA	
Temperature rise	115 °C	
Height	8.25 in (209.55 mm)	
Width	8.68 in (220.47 mm)	
Depth	6.56 in (166.62 mm)	
Enclosure mounting	Wall mounted	
Net Weight	30.1 Lb(US) (13.7 kg) 30.09 lb(US) (13.65 kg)	
Enclosure Material	Painted sheet steel	

Environment

Enclosure Type	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product Certifications	CSA[RETURN]cULus[RETURN]UL Listed

Ordering and shipping details

Category	US10PE216277
Discount Schedule	0PE2
GTIN	785901019879
Returnability	Yes
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	9.700 in (24.638 cm)	
Package 1 Width	11.0000000000 in (27.94 cm)	
Package 1 Length	12.800 in (32.512 cm)	
Package 1 Weight	36.910 lb(US) (16.742 kg)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☐ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes

Contractual warranty

141	40 (1
Warranty	18 months
· · · · · · · · · · · · · · · · · · ·	To monate