

Main

Range of product	9007
Series name	Heavy duty
Product or component type	Limit switch base
Device short name	9007C
Body type	Standard plug-in
Product compatibility	9007C
Electrical connection	Screw-clamp terminals AWG 22AWG 12), 12
Cable entry	1 entry for 1/2" - 14 NPT ANSI B1.20.1
Ambient air temperature for operation	-20185 °F (-2985 °C) standard environment
Environmental characteristic	Standard environment
Sale per indivisible quantity	1

Complementary

Associated head	9007C	
Associated connection component	9007CO62 9007CO66 9007CO68	
Body material	Zinc	
Function available	-	
Mechanical durability	10000000 cycles	
Maximum Width	1.55 in (39.37 mm)	
Height	3.14 in (79.76 mm)	
Maximum Depth	0.9 in (22.86 mm)	
Net Weight	1.06 lb(US) (0.48 kg)	

Environment

01 1 11	00 0 150 00000 0 07	
Shock resistance	60 gn 9 ms IEC 60068-2-27	
Vibration resistance	25 gn 10150 Hz)IEC 60068-2-6	
NEMA degree of protection	NEMA 1 Nema type 250	
	NEMA 2 Nema type 250	
	NEMA 4 Nema type 250	
	NEMA 6 Nema type 250	
	NEMA 6P Nema type 250	
	NEMA 12 Nema type 250	
	NEMA 13 Nema type 250	
IP degree of protection	IP67 IEC 60529	
Electrical shock protection class	Class 0 IEC 61140	
Ambient air temperature for storage	-20185 °F (-2985 °C)	
Protective treatment	Epoxy powder coat	

Ordering and shipping details

Category	21499 - 9007 C LIMIT SWITCHES
Discount Schedule	DS1
GTIN	00785901500896
Nbr. of units in pkg.	1
Package weight(Lbs)	0.48 lb(US) (0.22 kg)

Returnability	Yes
Country of origin	MX
Packing Units	
Unit Type of Package 1	PCE
Package 1 Height	1.60 in (4.064 cm)
Package 1 width	2.70 in (6.858 cm)
Package 1 Length	4.10 in (10.414 cm)
Offer Sustainability California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile
Contractual warranty	
Warranty	18 months