



Safety switch, general duty, fusible, 3 pole, 4 wire, 120/240VAC, 60A, Type 1 galv steel, with solid neut

CD322N

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type	Single Throw Safety Switch
Series name	General duty

Complementary

Line Rated Current	60 A	
Device Composition	Neutral (factory installed)	
Disconnector device type	Fusible disconnect	
Short-circuit current	100 kA maximum cartridge	
Device mounting	Surface	
Number of poles	3	
Electrical Connection	Lugs	
[Ue] rated operational voltage	120/240 V AC	
Motor power hp	7.5 hp at 240 V AC 50-60 Hz for 1 phase motors 15 hp at 240 V AC 50-60 Hz for 3 phase motors 15 hp at 240 V AC 50-60 Hz for 1 phase motors 30 hp at 240 V AC 50-60 Hz for 3 phase motors	
AWG gauge	AWG 14AWG 3 copper or aluminium	
Tightening torque	35 lbf.in (4.0 N.m) 0.0030.008 in² (2.085.26 mm²) (AWG 14AWG 10) 45 lbf.in (5.08 N.m) 0.01 in² (8.37 mm²) (AWG 8) 45 lbf.in (5.08 N.m) 0.020.03 in² (12.321.12 mm²) (AWG 6AWG 4) 50 lbf.in (5.6 N.m) 0.04 in² (26.67 mm²) (AWG 3)	
Height	14.6 in (370.8 mm)	
Width	7.45 in (189.23 mm)	
Depth	4.87 in (123.70 mm)	

Environment

Product Certifications	CSA	
NEMA degree of protection	NEMA 1 galvannealed steel	

Ordering and shipping details

Category	US1DE1A00154	
Discount Schedule	DE1A	
GTIN	785901404934	
Returnability	Yes	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Country of origin US

Packing Units

Unit Type of Package 1	PCE	
Nbr. of units in pkg.	1	
Package 1 Height	5.30 in (13.462 cm)	
Package 1 Width	7.80 in (19.812 cm)	
Package 1 Length	16.20 in (41.148 cm)	
Package weight(Lbs)	8.049 lb(US) (3.651 kg)	

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	43
Environmental Disclosure	Product Environmental Profile

Use Better

⊗ Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No