



Main breaker, QO, 150A, 2 pole, 120/240VAC, 22kA, bolt on

QOM2150VH

Product availability: Stock - Normally stocked in distribution

Main

Product	Miniature circuit-breaker
Range	QO
Current Rating	150 A
Voltage Rating	120/240 V AC 120 V AC
Mounting Type	Bolt-on
Number of Poles	2P
Circuit Breaker Type	Standard
Ratings	Primary main breaker
Electrical Connection	Lugs
Frame Size	QOM2

Complementary

Interrupt Rating	22 kA 120/240 V AC 22 kA 120 V AC	
Wire Size	AWG 4300 kcmil aluminium/copper	
Tightening Torque	53.1 lbf.in (6 N.m) 0.0060.1 in² (465 mm²) (AWG 12AWG 2/0)	
Height	5.6 in (142 mm)	
Width	3.6 in (91 mm)	
Depth	5.08 in (129 mm)	
Net Weight	2.650 lb(US) (1.202 kg)	
Load Center Type	Main breaker	
Number of Phases	1 phase	
For Use With	QO load center Homeline load center	
Breaker compatibility	Load center QO Load center Homeline	

Environment

Certifications	UL Listed CSA
Ambient Rating	104 °F (40 °C)

Ordering and shipping details

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Category	US1DE3A00100
Discount Schedule	DE3A
GTIN	785901004059
Returnability	Yes

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.40 in (11.176 cm)
Package 1 Width	5.60 in (14.224 cm)
Package 1 Length	6.40 in (16.256 cm)
Package weight(Lbs)	2.650 lb(US) (1.202 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	468
Package 2 Height	40.00 in (101.6 cm)
Package 2 Width	36.00 in (91.44 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	1216.801 lb(US) (551.931 kg)

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint		
Carbon footprint (kg CO2 eq, Total Life cycle)	254	

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	770cc9ea-53d2-4d3d-a57a-062b35abd847

Use Again

○ Repack and remanufacture		
Take-back	No	

Technical Illustration

Wiring diagram

