



Energy center, QO, 1 phase, 61 available circuits, 200A, PoN, ringed socket, semiflush, UG, solar, battery, gen ready

QOWC60M200PFY

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type	All-In-One	
Range of Product	QO	
Meter socket type	Ringed	
Provided equipment	Wiser Energy kit Miniature circuit breaker 1) 2P 15 A Miniature circuit breaker 1) 1P 20 A Miniature circuit breaker 2) 2P 110 A Surge protection device (SPD) Type 2 120/240 V Socket-outlet 1) 20 A	

Complementary

Line Rated Current	200 A	
Load current	120 A alternate energy back feed	
Number of Phases	1 phase	
Short-circuit current	22 kA	
Mounting	Semi flush	
Number of spaces	60	
Available number of spaces	51	
Number of circuits	70	
Available number of circuits	61	
Number of Tandem Breakers	10	
Electrical connection	Lugs, line side Lugs, service ground	
Wire Size	AWG 4250 kcmil (aluminium/copper) line side AWG 14AWG 2/0 (aluminium/copper) service ground	
Disconnect Rating	200 A	
Branch Breaker Rating	90 A	
Service feed location	UG	
Bypass type	No bypass	
Connections - Terminals	Plug-on neutral	
Color	Matte white	
Product Compatibility	Solar ready Battery ready Generator ready	
Width	28.5 in (723.9 mm)	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Depth	9.01 in (228.9 mm)	
Height	45.0000000000 in (1143 mm)	
Bus Rating	225.0 A	

Environment

NEMA Rating NEMA 3R

Ordering and shipping details

Category	US1DE3A00099	
Discount Schedule	DE3A	
GTIN	03606481064493	
Returnability	Yes	
Country of origin	MX	

Packing Units

_		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	19.88 in (50.483 cm)	
Package 1 Width	40.00 in (101.6 cm)	
Package 1 Length	55.00 in (139.7 cm)	
Package 1 Weight	184.999 lb(US) (83.914 kg)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	2	
Package 2 Height	34.75 in (88.265 cm)	
Package 2 Width	40.00 in (101.6 cm)	
Package 2 Length	55.00 in (139.7 cm)	
Package 2 Weight	5359.910 oz (151953.444 g)	



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg CO2 eq, Total Life cycle)	331
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Halogen content performance	Halogen free plastic parts product

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No

Product data sheet QOWC60M200PFY

Image of product / Alternate images

Alternative

Product data sheet QOWC60M200PFY





